

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 September 2001 (07.09.2001)

PCT

(10) International Publication Number  
**WO 01/65420 A2**

- (51) International Patent Classification<sup>7</sup>: **G06F 17/40**
- (21) International Application Number: **PCT/US01/06411**
- (22) International Filing Date: **28 February 2001 (28.02.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
- |            |                                |    |
|------------|--------------------------------|----|
| 60/185,668 | 29 February 2000 (29.02.2000)  | US |
| 60/229,241 | 30 August 2000 (30.08.2000)    | US |
| 60/233,340 | 18 September 2000 (18.09.2000) | US |
| 09/694,079 | 20 October 2000 (20.10.2000)   | US |
- (71) Applicant: **WATCHPOINT MEDIA, INC.** [US/US]; 129 South Street, Boston, MA 02111 (US).
- (72) Inventors: **SARACHIK, Karen**; 472 Walnut Street, Newton, MA 02460 (US). **DAKSS, Jon**; 158 Thorndike Street, Cambridge, MA 02141 (US). **BOVE, V., Michael, Jr.**; 57 Ray Road, Wrentham, MA 02093 (US). **WACHMAN, Josh**; 135 Pleasant Street, #505, Brookline, MA 02446 (US). **KATCHER, Dan**; 125 Brookside Road, Needham, MA 02492 (US).
- (74) Agent: **MILSTEIN, Joseph, B.**; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **METHODS FOR MANIPULATING DATA IN MULTIPLE DIMENSIONS**

**(57) Abstract:** A system and method of adding hyperlinked information to a television broadcast. The broadcast material is analyzed and one or more regions within a frame are identified. Additional information can be associated with a region, and can be transmitted in encoded form, using timing information to identify the frame with which the information is associated. The system comprising a video source and an encoder that produces a transport stream in communication with the video source, an annotation source, a data packet stream generator that produces encoded annotation data packets in communication with the annotation source and the encoder, and a multiplexer system in communication with the encoder and the data packet stream generator. The encoder provides timestamp information to the data packet stream generator and the data packet stream generator synchronizes annotation data from the annotation source with a video signal from the video source in response to the timestamp information. The multiplexer generates a digital broadcast signal that includes an augmented transport stream from the transport stream and the encoded data packets. A receiver displays the annotation information associated with the video signal in response to a viewer request on a frame by frame basis. A viewer can respond interactively to the material, including performing commercial transactions, by using a backchannel that is provided for interactive communication.

**WO 01/65420 A2**

## **METHODS FOR MANIPULATING DATA IN MULTIPLE DIMENSIONS**

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of U.S. provisional patent applications serial number 60/185,668, filed February 29, 2000, entitled "Interactive Hyperlinked Video System"; serial number 60/229,241, filed August 30, 2000, entitled "A Method and Apparatus for Hyperlinking in a Television Broadcast"; and serial number 60/233,340, filed September 18, 2000, entitled "A  
5 Method and Apparatus for Hyperlinking in a Television Broadcast." The entirety of each of said provisional patent applications is incorporated herein by reference. This application claims priority to a U.S. utility patent application Serial No. 09/694,079 filed October 20, 2000, which application is assignable to the same entity that holds assignment rights to this application.

### **FIELD OF THE INVENTION**

10 The invention relates to the field of broadcast television and more specifically to the field of manipulating data in multiple dimensions in a hyperlinked television broadcast.

### **BACKGROUND OF THE INVENTION**

Broadcasts of information via television signals are well known in the prior art.

Television broadcasts are unidirectional, and do not afford a viewer an opportunity to interact  
15 with the material that appears on a television display. Viewer response to material displayed using a remote control is known but is generally limited to selecting a program for viewing from a listing of available broadcasts. In particular, it has proven difficult to create hyperlinked television programs in which information is associated with one or more regions of a screen. The present invention addresses this need.

- 2 -

**SUMMARY OF THE INVENTION**

The invention provides methods and systems for augmenting television broadcast material with information that is presented to a viewer in an interactive manner.

In one aspect, the invention relates to a method of analyzing elements of a three-dimensional array. The method comprises defining a subset of a three-dimensional array, the subset having a plurality of sequential two-dimensional arrays containing elements for analysis, wherein the elements within the two-dimensional arrays are represented by a first axis and a second axis, the first and second axes being two non-collinear axes and the third dimension corresponding to an axis orthogonal to the first and second axes. The method comprises defining at least one region within a two-dimensional array, the at least one region having at least one element for analysis, defining a morphological mask having two dimensions and having at least one element, the morphological mask having at least one set element and at least one test element, and defining a two-dimensional output array corresponding to a selected two-dimensional array containing elements for analysis. The method comprises orienting the morphological mask with respect to the selected two-dimensional array containing the region having elements for analysis and with respect to at least one of a predecessor two-dimensional array and a successor two-dimensional array. The method comprises computing, using a mathematical operation, a result based on the properties of the at least one set element and the corresponding elements of the selected two-dimensional array containing elements for analysis and the at least one of a predecessor two-dimensional array and a successor two-dimensional array. The method comprises plotting the computed result in the two-dimensional output array at one or more elements corresponding to the at least one test element of the morphological mask. The method comprises repeating the steps of orienting, computing and plotting while moving the morphological mask stepwise along the first axis and the second axis over the region having elements for analysis until every element of the region has been analyzed.

- 3 -

In one embodiment, the method further comprises repeating the steps of defining a two-dimensional output array, and repeatedly orienting, computing, and plotting until every region within successive two-dimensional arrays of the three-dimensional subset has been analyzed. In one embodiment, the first axis and the second axis representing elements within the two-dimensional arrays are rows and columns. In one embodiment, the two-dimensional arrays are video frames. In one embodiment, the third dimension corresponding to an axis orthogonal to the first and second axes represents time. In one embodiment, the third dimension corresponding to an axis orthogonal to the first and second axes represents frame sequence numbers. In one embodiment, the mathematical operation corresponds to taking the highest incidence of occurrence in a histogram. In one embodiment, the mathematical operation corresponds to assigning a value if and only if the value is the only value that appears at elements corresponding to the at least one test element of the morphological mask. In one embodiment, the method further comprises recording the plotted result as a computer-readable file. In one embodiment, the method further comprises displaying the plotted result.

In one aspect, the invention features a method for filling a connected three-dimensional digital volume. The method comprises selecting a plurality of sequential two-dimensional sections that contain the volume, the two dimensional sections disposed orthogonally to a third dimension, each two-dimensional section containing locations identified by a first coordinate and a second coordinate; defining a plurality of regions in at least one of the two-dimensional sections, each region comprising at least one location; selecting a first region in one of the at least one of the two-dimensional sections, the region included within the volume to be filled with a selected symbol; filling the selected first region with the selected symbol; moving in a first direction along the third dimension to the successive two-dimensional section; determining whether a location in the successive two-dimensional section corresponding to a filled location in the one of the at least one of the two-dimensional sections belongs to the volume; if there is a



- 4 -

positive outcome of the determination step, filling a region that includes the location in the successive two-dimensional section with the selected symbol; and beginning with the newly-filled region in the successive two-dimensional section, repeating the moving, determining and filling steps recited immediately heretofore until the determining step results in a negative outcome; and upon a negative outcome of any determining step heretofore, returning to the first region, and, moving along the third dimension in a direction opposite to the first direction, repeating the steps of moving, determining and filling as stated above until a negative outcome results for a determining step.

In one embodiment, the two-dimensional sections comprise images. In one embodiment, the first coordinate and the second coordinate define the location of a pixel. In one embodiment, the first coordinate and the second coordinate define rows and columns of an image. In one embodiment, the third dimension comprises time. In one embodiment, the symbol represents a visual effect when rendered on a display.

In another aspect, invention relates to a method of generating an outline of a two-dimensional region, comprising the steps of (a) defining a two-dimensional region within a two-dimensional array containing elements represented by a first axis and a second axis that is non-collinear with the first axis; (b) defining a morphological mask having at least two dimensions and having at least one element, the morphological mask having at least one set element and at least one test element; (c) defining a two-dimensional output array corresponding to the two-dimensional array containing the region; (d) orienting the morphological mask with respect to the two-dimensional array containing the region; (e) computing a result based on the properties of the at least one set element of the morphological mask and the corresponding elements of the two-dimensional array containing the region, the result being to turn off the test elements of the morphological mask if and only if a condition selected from the group of conditions consisting of all of the set elements of the mask are in positions corresponding to elements of the region and

- 5 -

none of the set elements of the mask are in positions corresponding to elements of the region is true, and the result being to set the test elements of the morphological mask otherwise; (f) plotting the computed result in the two-dimensional output array at one or more elements corresponding to the at least one test element of the morphological mask; and (g) repeating steps 5 (e) and (f) while moving the morphological mask stepwise along the first axis and the second axis over the portion of the two-dimensional array containing the region until every element of the region has been analyzed.

In one embodiment, the first axis and the second axis representing elements within the two-dimensional arrays are rows and columns. In one embodiment, the two-dimensional arrays 10 are video frames. In one embodiment, the method further comprise recording the plotted result as a computer-readable file. In one embodiment, the morphological mask comprises a square array having an odd number of elements, and the test element is the center element. In one embodiment, the elements of the morphological mask are pixels.

In yet another aspect, the invention features a method of generating an outline of at least 15 one two-dimensional region, comprising the steps of (a) defining a plurality of two-dimensional regions within a two dimensional array containing elements represented by a first axis and a second axis that is non-collinear with the first axis; (b) defining a morphological mask having at least two dimensions and having at least one element, the morphological mask having at least one set element and at least one test element; (c) defining a two-dimensional output array 20 corresponding to the two-dimensional array containing the plurality of regions; (d) selecting at least one of the plurality of regions, each of the selected regions to have an outline generated therefor; (e) orienting the morphological mask with respect to the two-dimensional array containing the plurality of regions; (f) computing a result based on the properties of the at least one set element of the morphological mask and the corresponding elements of the two- 25 dimensional array containing the plurality of regions, the result being to turn off the test elements

- 6 -

of the morphological mask if and only if a condition selected from the group of conditions consisting of all of the set elements of the mask are in positions corresponding to elements of the at least one selected region and none of the set elements of the mask are in positions corresponding to elements of the at least one selected region is true, and the result being to set the test elements of the morphological mask otherwise; (g) plotting the computed result in the two-dimensional output array at one or more elements corresponding to the at least one test element of the morphological mask; and (h) repeating steps (f) and (g) while moving the morphological mask stepwise along the first axis and the second axis over the portion of the two-dimensional array containing the at least one selected region until every element of the at least one selected region has been analyzed.

In one embodiment, the first axis and the second axis representing elements within the two-dimensional arrays are rows and columns. In one embodiment, the two-dimensional arrays are video frames. In one embodiment, the method further comprises recording the plotted result as a computer-readable file. In one embodiment, the morphological mask comprises a square array having an odd number of elements, and the test element is the center element. In one embodiment, the elements of the morphological mask are pixels.

In still another aspect, the invention relates to a method of encoding at least a portion of an image, comprising the steps of (a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance; (b) analyzing axis-wise the pixels to determine sequences of pixels having substantially identical appearance; (c) comparing a sequence of pixels occurring along a first axis-wise traverse with a sequence of pixels occurring along a successive axis-wise traverse; (d) in the event that the comparison discloses two or more successive traverses having an identical number of distinct appearances in an identical progression, recording a number corresponding to the number of such successive traverses, recording for the first traverse a series of ordered pairs comprising a first value

representing the appearance and a second value representing the number of successive pixels having the appearance, and recording for each successive traverse a series of values corresponding to the second value of each ordered pair; (e) in the event that the comparison fails to disclose two or more successive traverses having an identical number of distinct appearances in an identical progression, recording the number one and recording for the traverse a series of ordered pairs comprising a first value representing the appearance and a second value representing the number of successive pixels having the appearance; and (f) repeating steps (c), (d) and (e) until the pixels of the region are completely encoded. In one embodiment, the axis-wise traverse comprises traversing a selected one of a row and a column.

10 In a further aspect, the invention relates to a method of decoding an encoded image, comprising the steps of (a) reading from a memory a location of a region within an image, the region defined by one or more pixels at locations identifiable by two non-collinear axes, each pixel having an appearance; (b) reading from the memory a number corresponding to the number of successive traverses along one of the two non-collinear axes, the traverses having an identical number of distinct appearances in an identical progression; (c) reading a series of ordered pairs comprising a first value representing an appearance and a second value representing the number of successive pixels having the appearance; (d) rendering pixels along the traverse according to the series of ordered pairs; (e) in the event that the number read in step (b) is greater than one, repeating a number of times equal to the number read in step (b) reduced by one the steps of (1) reading from memory a series of values corresponding to the second value of each ordered pair read in step (c); and (2) for each such value read in step (e)(1), rendering a sequences of pixels corresponding to the second value, each pixel having an appearance corresponding to the first value of the ordered pair read in step (c); and (f) repeating steps (b) through (e) until the pixels of the region are completely rendered.

- 8 -

In one embodiment, the axis-wise traverse comprises traversing a selected one of a row and a column. In one embodiment, rendering a pixel comprises displaying the pixel using at least one of a color, a brightness, a blinking, a flashing, and a display mode. In one embodiment, the method further comprises the step of recording on a computer-readable medium a representation  
5 of the rendering of pixels in the region.

In a yet further aspect, the invention features a method of encoding at least a portion of an image, comprising the steps of (a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance; (b) analyzing axis-wise the pixels to determine sequences of pixels having substantially identical appearance; (c ) in the  
10 event that the analysis discloses two or more successive pixels having identical appearance, recording a series of ordered triples comprising a first value representing the appearance, a second value representing the number of successive pixels having the appearance, and a third value representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position.

15 In one embodiment, defining two non-collinear axes comprises defining a row and a column. In one embodiment, analyzing a pixel to determine an appearance comprises analyzing for at least one of a color, a brightness, and a display mode.

In a still further aspect, the invention relates to a method of decoding at least a portion of an image, comprising the steps of: (a) defining a region of an image having pixels at locations  
20 identifiable by two non-collinear axes, each pixel having an appearance; (b) reading a series of ordered triples comprising a first value representing the appearance, a second value representing the number of successive pixels having the appearance, and a third value representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position; and (c ) for each ordered triple, rendering pixels in the region using the

appearance the number of successive pixels having the appearance beginning at the starting position with respect to a pixel at a known position.

In one embodiment, defining two non-collinear axes comprises defining a row and a column. In one embodiment, rendering a pixel comprises displaying the pixel using at least one of a color, a brightness, a blinking, a flashing, and a display mode. In one embodiment, the method further comprises the step of recording on a computer-readable medium a representation of the rendering of pixels in the region.

In still another aspect, the invention features a method of encoding at least a portion of an image, comprising the steps of (a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance; (b) defining pixels in the image that represent a background, the background having a characteristic background appearance; (c) comparing a sequence of pixels occurring along a first axis-wise traverse with a sequence of pixels occurring along a successive axis-wise traverse; (d) in the event that the comparison discloses two or more successive traverses having an identical number of distinct appearances in an identical progression: (1) recording a number N corresponding to the number of such successive traverses; (2) for the first of such successive traverses, recording for each sequence of pixels having a distinct appearance different from the characteristic background appearance an ordered triple comprising a first value representing the appearance, a second value representing the number of successive pixels having the appearance, and a third value representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position; (3) for the following of the N minus one traverses, recording for each sequence of pixels having a distinct appearance different from the characteristic background appearance an ordered double comprising a first quantity representing the number of successive pixels having the appearance indicated by the first value of the ordered triple recorded for the corresponding sequence of pixels in the first traverse, and a second

- 10 -

quantity representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position; (e) in the event that the comparison fails to disclose two or more successive traverses having an identical number of distinct appearances in an identical progression, recording the number one and recording for the traverse a series of ordered  
5 triples comprising a first value representing an appearance different from the characteristic background appearance, a second value representing the number of successive pixels having the appearance, and a third value representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position; and (f) repeating steps (c), (d) and (e) until the pixels of the region having an appearance different from the characteristic  
10 background appearance are completely encoded.

In one embodiment, defining two non-collinear axes comprises defining a row and a column. In one embodiment, analyzing a pixel to determine an appearance comprises analyzing for at least one of a color, a brightness, and a display mode.

In an additional aspect, the invention relates to a method of decoding at least a portion of  
15 an image, comprising the steps of (a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance; (b) defining a characteristic background appearance; (c) reading from a record a number N corresponding to a number of successive traverses having an identical number of distinct appearances in an identical progression; (d) if the number N is one: (1) reading for the traverse a series of ordered triples  
20 comprising a first value representing an appearance different from the characteristic background appearance, a second value representing the number of successive pixels having the appearance, and a third value representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position; and (2) for each ordered triple, rendering with the appearance the number of successive pixels having the appearance beginning at the starting  
25 position with respect to a pixel at a known position; (e) if the number N is greater than one, for

the first traverse, performing steps (d)(1) and (d)(2), and for each traverse of the further N minus one traverses: (1) reading for each traverse a series of ordered doubles comprising a first quantity representing the number of successive pixels having the appearance indicated by the first value of the ordered triple recorded for the corresponding sequence of pixels in the first traverse, and a  
5 second quantity representing an offset defining a starting position of the two or more successive pixels with respect to a pixel at a known position; and (2) for each ordered double, rendering with the appearance the number of successive pixels having the appearance beginning at the starting position with respect to a pixel at a known position; (f) repeating steps (c), (d) and (e) until the pixels of the region having an appearance different from the characteristic background  
10 appearance are completely encoded. and (g) for any pixel in the region of the image that has not been rendered in steps (d), (e) and (f), rendering the pixel using a characteristic background appearance.

In one embodiment, defining two non-collinear axes comprises defining a row and a column. In one embodiment, rendering a pixel comprises displaying the pixel using at least one  
15 of a color, a brightness, a blinking, a flashing, and a display mode. In one embodiment, the method further comprises the step of recording on a computer-readable medium a representation of the rendering of pixels in the region.

The foregoing and other objects, aspects, features, and advantages of the invention will become more apparent from the following description and from the claims.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

20 Figs. 1A-1D depict a series of frames of video as produced by the system of the invention;

Fig. 2 is a block diagram of an embodiment of a hyperlinked video system constructed in accordance with the invention;

25 Fig. 2A is a block diagram of the flow of data in the embodiment of the system shown in Fig. 2;



- 12 -

Fig. 2B is a diagram of a mask packet set;

Fig. 2C is a diagram of an initial encoded data packet stream;

Fig. 2D is a diagram of a final encoded data packet stream;

Fig. 3 is a block diagram of an embodiment of the multiplexer system shown in Fig 1;

5 Fig. 4 is a block diagram of an embodiment of the digital receiver shown in Fig. 2;

Fig. 5 is a diagram of an embodiment of the data structures used by the system of Fig. 2 to store annotation data;

Fig. 5A is a block diagram of an object properties table data structure and a program mapping table data structure;

10 Fig. 6 is a state diagram of the data flow of an embodiment of the system shown in Fig. 2;

Fig. 7 depicts the interactions between and among states within the state machine depicted in Fig. 6 of an embodiment of the invention;

Figs. 8A through 8G depict schematically various illustrative examples of embodiments of an interactive content icon according to the invention;

15 Figs. 9A through 9D depict illustrative embodiments of compression methods for video images, according to the principles of the invention;

Fig. 10A shows an exemplary region of a frame and an exemplary mask, that are used to describe a two-dimensional image in the terms of mathematical morphology, according to the invention;

20 Fig. 10B shows an exemplary resultant image of a two-dimensional mathematical morphology analysis, and a single resultant pixel, according to the principles of the invention; and

Fig. 11A shows a sequence of exemplary frames and an exemplary mask, that are used to describe a three-dimensional image in the terms of mathematical morphology using time as a  
25 dimension, according to the invention;

- 13 -

Fig. 11B shows an exemplary resultant frame of a three-dimensional mathematical morphology analysis using time as a dimension, and a single resultant pixel, according to the principles of the invention;

Fig. 11C is a flow diagram showing an illustrative process by which three-dimensional floodfill is accomplished, according to one embodiment of the invention;

Fig. 12 is a diagram showing an exemplary application of mathematical morphology analysis that creates an outline of a region, according to the principles of the invention; and

Fig. 13 is a diagram showing three illustrative examples of the evolutions of histograms over successive frames that are indicative of motion, according to the invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENT

In brief overview, the invention provides a way for annotation information to be associated with objects displayed in the frames of a broadcast video and displayed upon command of a viewer. For example, referring to Fig. 1, annotation information, in the form of store, price and availability information may be associated with a specific shirt 2 worn by an actor in a television broadcast (Fig. 1A). To achieve this, the shirt 2 is first identified to the system by a designer operating a portion of the system called the authoring system. The designer identifies 3 the shirt 2 in a given frame, for example by coloring in the shirt (Fig. 1B), and the system keeps track of the location of the shirt 2 in the preceding and subsequent frames. The designer also generates the text that becomes the annotation data 5 associated with the shirt 2. Thus in this example the annotation data may include the names of stores in which the shirt 2 may be purchased, the price of the shirt 2 and the colors available. The system then denotes that the shirt 2 has annotation data associated with it, for example by outlining 4 the shirt 2 in a different color within the frame (Fig. 1C).

When the show is broadcast to a viewer by the transmission portion of the system, not only is the video broadcast, but also the mask which outlines the shirt 2 and the annotation data which accompanies the shirt 2. The receiver portion of the system at the viewer's location

- 14 -

receives this data and displays the video frames along with masks that outline the objects which have associated annotation data. In this example the shirt 2 in the video frame is outlined. If the viewer of the broadcast video wishes to see the annotation data, he or she simply uses the control buttons on a standard remote control handset to notify the receiver portion of the system that the display of annotation data is desired. The system then displays the annotation data 5 on the screen along with the object (Fig. 1D). In this way denoted objects act as hyperlinks to additional information.

Referring to Fig. 2, a hyperlinked video broadcast system constructed in accordance with the invention includes a transmission portion 10, a communications channel portion 12 and a reception portion 14. The transmission portion 10 includes a video source 20, an authoring tool 24, a database storage system 28 and a transmitter 32. The video source 20 in various embodiments is a video camera, a video disk, tape or cassette, a video feed or any other source of video known to one skilled in the art. The authoring tool 24, which is an annotation source, receives video data from the video source 20 and displays it for a video designer to view and manipulate as described below. Annotation data, for example, the text to be displayed with the video image, is stored in an object database 28 and sent to the transmitter 32 for transmission over the communications channel portion 12 of the system.

The transmitter 32 includes a video encoder 36, a data packet stream generator 40, and a multiplexer (mux) 44 which combines the signals from the video encoder 36 and the data packet stream generator 40 for transmission over the communications channel 12. The video encoder 36 may be any encoder, such as an MPEG or MPEG2 encoder, for producing a transport stream, as is known to one skilled in the art. The data packet stream generator 40 encodes additional data, as described below, which is to accompany the video data when it is transmitted to the viewer. The data packet stream generator 40 generates encoded data packets. The mux 44 produces an augmented transport stream.

The communications channel portion 12 includes not only the transmission medium such as cable, terrestrial broadcast infrastructure, microwave link, or satellite link, but also any intermediate storage which holds the video data until received by the reception portion 14. Such intermediate broadcast storage may include video disk, tape or cassette, memory or other storage devices known to one skilled in the art. The communications channel portion also includes the headend transmitter 50, supplied by a multiple services operator.

The reception portion 14 includes a digital receiver 54, such as a digital settop box, which decodes the signals for display on the television display 58. The digital receiver hardware 54 is any digital receiver hardware 54 known to one skilled in the art.

In operation and referring also to Fig. 2A, a designer loads video data 22 from a video source 20 into the authoring tool 24. The video data 22 is also sent from the video source 20 to the video encoder 36 for encoding using, for example, the MPEG standard. Using the authoring tool 24 the designer selects portions of a video image to associate with screen annotations. For example, the designer could select a shirt 2 worn by an actor in the video image and assign annotation data indicating the maker of the shirt 2, its purchase price and the name of a local distributor. Conversely, annotation data may include additional textual information about the object. For example, annotation data in a documentary program could have biographical information about the individual on the screen. The annotation data 5 along with information about the shape of the shirt 2 and the location of the shirt 2 in the image, which is the mask image, as described below, are stored as data structures 25, 25' in a database 28.

Once a designer has authored a given program, the authoring tool determines the range over which objects appear and data structures are utilized in the annotated program. This information is used by the current inventive system to ensure that the data enabling viewer interactions with an object is transmitted before the object is presented to the viewer. This

- 16 -

information is also used by the current inventive system to determine when data is no longer required by a program and can be erased from the memory 128 discussed below.

As described above, this annotation data is also sent to the data packet stream generator 40 for conversion into an encoded data packet stream 27. Time stamp data in the transport stream 29 from the video encoder 36 is also an input signal into the data packet stream generator 40 and is used to synchronize the mask and the annotation data with the image data. The data packet stream generator 40 achieves the synchronization by stepping through a program and associating the timing information of each frame of video with the corresponding mask. Timing information can be any kind of information that allows the synchronization of video and mask information. For example, timing information can be timestamp information as generated by an MPEG encoder, timecode information such as is provided by the SMPTE timecode standard for video, frame numbering information such as a unique identifier for a frame or a sequential number for a frame, the global time of day, and the like. In the present illustration of the invention, timestamp information will be used as an exemplary embodiment.

The encoded video data from the video encoder 36 is combined with the encoded data packet stream 27 from the data packet stream generator 40 in a multiplexer 44 and the resulting augmented transport stream 46 is an input to a multiplexer system 48. In this illustrative embodiment the multiplexer system 48 is capable of receiving additional transport 29' and augmented transport 46'' streams. The transport 29' and augmented transport 46' streams include digitally encoded video, audio, and data streams generated by the system or by other methods known in the art. The output from the multiplexer system 48 is sent to the communications channel 12 for storage and/or broadcast. The broadcast signal is sent to and received by the digital receiver 54. The digital receiver 54 sends the encoded video portion of the multiplexed signal to the television 58 for display. The digital receiver 54 also accepts commands from a viewer, using a handheld remote control unit, to display any annotations that

accompany the video images. In one embodiment the digital receiver 54 is also directly in communication with an alternative network connection 56 (Fig. 2).

In an alternative embodiment, information from the object database 28 is transferred to a second database 30 in Fig. 2 for access through a network 31, such as the Internet, or directly to a database 33. In this embodiment the headend 50 accesses the annotation object data stored on the second database 30 when so requested by the viewer. This arrangement is useful in cases such as when the viewer has recorded the program for viewing at a later time and the recording medium cannot record the annotation data, or when the data cannot be transmitted in-band during the program. Thus when the recorded image is played back through the digital receiver 54, and the viewer requests annotation data, the digital receiver 54 can instruct the headend 50 to acquire the data through the network 31. In addition, the headend 50, under the command of the digital receiver 54, would be able to write data to a database 33 on the network 31 or to a headend database 52. Such data written by the headend 50 may be marketing data indicating which objects have been viewed or it could be order information required from the viewer to order the displayed item over the network. A third embodiment combines attributes of the preceding embodiments in that some of the information is included in the original broadcast and some is retrieved in response to requests by the viewer.

In more detail with respect to the encoded data packet stream 27, and referring to Figs. 2B, 2C, and 2D, the data packet stream generator 40 is designed to generate a constant data rate stream despite variations in the size of the mask data and annotation data corresponding to the video frames. The data packet stream generator 40 achieves this through a three step process. First the data packet stream generator 40 determines an acceptable range of packet rates which can be inputted into the multiplexer 44. Next, the data packet stream generator 40 determines the number of packets filled by the largest mask in the program being encoded. This defines the number of packets in each mask packet set 39. That is, the number of packets that are allocated

- 18 -

for the transport of each mask. In the example shown in Figs. 2B, 2C, and 2D there are eight packets in each mask packet set 39. Using this number, the data packet stream generator 40 generates an initial version of the encoded data packet stream 27', allocating a fixed number of packets for each mask. If the number of packets required to hold a particular mask is less than the fixed number, then the data packet stream generator 40 buffers the initial encoded data packet stream 27' with null packets. The number of null packets depends on the number of packets remaining after the mask data has been written. In Fig. 2C the mask data 42 for frame 1000 fills four packets thereby leaving four packets to be filled by null packets. Similarly the data 42', 42'', 42''', for mask 999, mask 998, and mask 997 require three, five and two packets respectively. This leaves five, three, and six packets respectively to be filled by null packets.

Lastly, the data packet stream generator 40 generates the final encoded data packet stream 27'' by adding the object data. The data packet stream generator 40 does this by determining, from information provided by the authoring tool 24, the first occurrence that a given object has in a program. Data corresponding to that object is then inserted into the initial encoded data packet stream 27' starting at some point before the first occurrence of that object. The data packet stream generator 40 steps backwards through the initial encoded data packet stream 27' replacing null packets with object data as necessary. For example, in Fig. 2D object 98 is determined to appear in frame 1001. This means that all of the data associated with object 98 must arrive before frame 1001. The data 43 for object 98 fills five packets, O98A, O98B, O98C, O98D, and O98E, and has been added to the sets of packets allocated to mask data 1000 and mask data 999. The data 43' for object 97 fills two packets, O97A and O97B, and has been added to the set of packets allocated to mask data 998.

To facilitate the process of extracting data from the transport stream in one embodiment, the multiplexer 44 associates the mask data and the object data with different packet identifiers (PIDs) as are used to identify elementary streams in the MPEG2 standard. In this way the digital

receiver 54 can route mask and object data to different computing threads based solely on their PIDs, thereby eliminating the need to perform an initial analysis of the contents of the packets.

In reassembling the masks and object data, the digital receiver 54 is able to extract the appropriate number of packets from the stream because this information is provided by the data packet stream generator 40 as part of the encoding process. For example referring to Fig. 2D, the data packet stream generator 40 would specify that the mask 1000 filled four packets 42 and that the data 43 for object 98 filled five packets. This data is included in a header 38, 38', 38'', 38''' portion of the packet which occupies the first sixteen bytes of the first packet of each mask packet set.

As shown in an enlarged view of the mask header 38 in Fig. 2D, the header packet includes information relating to the number of packets carrying mask information, encoding information, timestamp information, visibility word information, and the unique identifier (UID) of the object mapping table associated with the particular mask. UIDs and object mapping tables are discussed below in more detail with respect to Fig. 5. Similarly, the first packet for each object begins with a sixteen byte header 45, 45' that contains information that enables the digital receiver 54 to extract, store and manipulate the data in the object packets 43, 43'. Also, as shown in an enlarged view of the object data header 45 in Fig. 2D, the object data header information includes the number of packets carrying data for the particular object, the object's data type, the object's UID, and timestamp related information such as the last instance that the object data is used in the program. The type of data structures employed by the system and the system's use of timestamps is discussed below in more detail with respect to figs. 5, 6, and 7.

Referring to Fig. 3, the multiplexer system 8' is an enhanced version of the multiplexer system shown in Fig. 2A. The multiplexer system 48' is capable of taking multiple transport 29' and augmented transport streams 46, 46'' as inputs to produce a single signal that is passed to the broadcast medium. The illustrative multiplexer system 44' includes three transport stream



- 20 -

5 multiplexers 60, 60', 60'', three modulators 68, 68', 68'', three upconverters 72, 72', 72'' and a mixer 78. The multiplexer system 44' includes three duplicate subsystems for converting multiple sets of transport streams into inputs to a mixer 78. Each subsystem includes a multiplexer 60, 60', 60'' for combining a set of transport streams (TS1 to TSN), (TS1' to TSN'), (TS1'' to TSN'') into a single transport stream (TS, TS', TS'') to be used as the input signal to a digital modulator (such as a Quadrature Amplitude Modulator (QAM) in the case of a North American digital cable system or an 8VSB Modulator in the case of terrestrial broadcast) 68, 68', 68''. In one embodiment each of the transport streams, for example TS1 to TSN, represent a television program. The output signal of the modulator 68, 68', 68'' is an intermediate frequency input signal to an upconverter 72, 72', 72'' which converts the output signal of the modulator 68, 68', 68'' to the proper channel frequency for broadcast. These converted channel frequencies are the input frequencies to a frequency mixer 78 which places the combined signals onto the broadcast medium.

15 Referring to Fig. 4, the digital receiver 54 includes a tuner 100 for selecting the broadcast channel of interest from the input broadcast stream and producing an intermediate frequency (IF) signal which contains the video and annotation data for the channel. The IF signal is an input signal to a demodulator 104 which demodulates the IF signal and extracts the information into a transport stream (TS). The transport stream is the input signal to a video decoder 108, such as an MPEG decoder. The video decoder 108 buffers the video frames received in a frame buffer 112. 20 The decoded video 114 and audio 116 output signals from the decoder 108 are input signals to the television display 58.

The annotation data is separated by the video decoder 108 and is transmitted to a CPU 124 for processing. The data is stored in memory 128. The memory also stores a computer program for processing annotation data and instructions from a viewer. When the digital 25 receiver 54 receives instructions from the viewer to display the annotated material, the

annotation data is rendered as computer graphic images overlaying some or all of the frame buffer 112. The decoder 108 then transmits the corresponding video signal 114 to the television display 58.

For broadcasts carried by media which can carry signals bi-directionally, such as cable or optical fiber, a connection can be made from the digital receiver 54 to the headend 50 of the broadcast system. In an alternative embodiment for broadcasts carried by unidirectional media, such as conventional television broadcasting or television satellite transmissions, a connection can be made from the digital receiver 54 to the alternative network connection 56 that communicates with a broadcaster or with another entity, without using the broadcast medium.

Communication channels for communication with a broadcaster or another entity that are not part of the broadcast medium can be telephone, an internet or similar computer connection, and the like. It should be understood that such non-broadcast communication channels can be used even if bi-directional broadcast media are available. Such communication connections, that carry messages sent from the viewer's location to the broadcaster or to another entity, such as an advertiser, are collectively referred to as backchannels.

Backchannel communications can be used for a variety of purposes, including gathering information that may be valuable to the broadcaster or to the advertiser, as well as allowing the viewer to interact with the broadcaster, the advertiser or others.

In one embodiment the digital receiver 54 generates reports that relate to the viewer's interaction with the annotation information via the remote control device. The reports transmitted to the broadcaster via the backchannel can include reports relating to operation of the remote, such as error reports that include information relating to use of the remote that is inappropriate with regard to the choices available to the viewer, such as an attempt to perform an "illegal" or undefined action, or an activity report that includes actions taken by the viewer that are tagged to show the timestamp of the material that was then being displayed on the television

- 22 -

display. The information that can be recognized and transmitted includes a report of a viewers' actions when advertiser-supplied material is available, such as actions by the viewer to access such material, as well as actions by the viewer terminating such accession of the material, for example, recognizing the point at which a viewer cancels an accession attempt. In some  
5 embodiments, the backchannel can be a store-and-forward channel.

The information that can be recognized and transmitted further includes information relating to a transaction that a viewer wishes to engage in, for example, the placing of an order for an item advertised on a broadcast (e.g., a shirt) including the quantity of units, the size, the color, the viewer's credit information and/or Personal Identification Number (PIN), and shipping  
10 information. The information that can be recognized and transmitted additionally includes information relating to a request for a service, for example a request to be shown a pay-per-view broadcast, including identification of the service, its time and place of delivery, payment information, and the like. The information that can be recognized and transmitted moreover includes information relating to non-commercial information, such as political information,  
15 public broadcasting information such as is provided by National Public Radio, and requests to access data repositories, such as the United States Patent and Trademark Office patent and trademark databases, and the like.

The backchannel can also be used for interactive communications, as where a potential purchaser selects an item that is out of stock, and a series of communications ensues regarding  
20 the possibility of making an alternative selection, or whether and for how long the viewer is willing to wait for the item to be restocked. Other illustrative examples of interactive communication are the display of a then current price, availability of a particular good or service (such as the location of seating available in a stadium at a specific sporting event, for example, the third game of the 2000 World Series), and confirmation of a purchase.

When a viewer begins to interact with the annotation system, the receiver 54 can set a flag that preserves the data required to carry out the interaction with the viewer for so long as the viewer continues the interaction, irrespective of the programmatic material that may be displayed on the video display, and irrespective of a time that the data would be discarded in the absence of the interaction by the viewer. In one embodiment, the receiver 54 sets an "in use bit" for each datum or data structure that appears in a data structure that is providing information to the viewer. A set "in use bit" prevents the receiver 54 from discarding the datum or data structure. When the viewer terminates the interaction, the "in use bit" is reset to zero and the datum or data structure can be discarded when its period of valid use expires. Also present in the data structures of the system but not shown in Fig. 5 is a expiration timestamp for each data structure by which the system discards that data structure once the time of the program has passed beyond the expiration timestamp. This discarding process is controlled by a garbage collector 532.

In the course of interacting with the annotation system, a viewer can create and modify a catalog. The catalog can include items that the viewer can decide to purchase as well as descriptions of information that the viewer wishes to obtain. The viewer can make selections for inclusion in the catalog from one or more broadcasts. The viewer can modify the contents of the catalog, and can initiate a commercial transaction immediately upon adding an item to the catalog, or at a later time.

The catalog can include entry information about a program that the viewer was watching, and the number of items that were added to the catalog. At a highest level, the viewer can interact with the system by using a device such as a remote control to identify the item of interest, the ordering particulars of interest, such as quantity, price, model, size, color and the like, and the status of an order, such as immediately placing the order or merely adding the item selected to a list of items of interest in the catalog.

- 24 -

At a further level of detail, the viewer can select the entry for the program, and can review the individual entries in the catalog list, including the status of the entry, such as "saved" or "ordered." The entry "saved" means that the item was entered on the list but was not ordered (i.e., the data pertaining to the item have been locked), while "ordered," as the name indicates, implies that an actual order for the item on the list was placed via the backchannel. The viewer can interrogate the list at a still lower level of detail, to see the particulars of an item (e.g., make, model, description, price, quantity ordered, color, and so forth). If the item is not a commercial product, but rather information of interest to the viewer, for example, biographical information about an actor who appears in a scene, an inquiry at the lowest level will display the information.

10 In one embodiment, navigation through the catalog is performed by using the remote control.

The viewer can set up an account for use in conducting transactions such as described above. In one embodiment, the viewer can enter information such as his name, a delivery address, and financial information such as a credit card or debit card number. This permits a viewer to place an order from any receiver that operates according to the system, such as a receiver in the home of a friend or in a hotel room. In another embodiment, the viewer can use an identifier such as a subscription account number and a password, for example the subscription account number associated with the provision of the service by the broadcaster. In such a situation, the broadcaster already has the home address and other delivery information for the viewer, as well as an open financial account with the viewer. In such an instance, the viewer simply places an order and confirms his or her desires by use of the password. In still another embodiment, the viewer can set up a personalized catalog. As an example of such a situation, members of a family can be given a personal catalog and can order goods and services up to spending limits and according to rules that are pre-arranged with the financially responsible individual in the family.

Depending on the location of the viewer and of the broadcast system, the format of the information conveyed over the backchannel can be one of QPSK modulation (as is used in the United States), DVB modulation (as is used in Europe), or other formats. Depending on the need for security in the transmission, the messages transmitted over the backchannel can be encrypted in whole or in part, using any encryption method. The information communicated over the backchannel can include information relating to authentication of the sender (for example, a unique identifier or a digital signature), integrity of the communication (e.g., an error correction method or system such as CRC), information relating to non-repudiation of a transaction, systems and methods relating to prevention of denial of service, and other similar information relating to the privacy, authenticity, and legally binding nature of the communication.

Depending on the kind of information that is being communicated, the information can be directed to the broadcaster, for example, information relating to viewer responses to broadcast material and requests for pay-per-view material; information can be directed to an advertiser, for example, an order for a shirt; and information can be directed to third parties, for example, a request to access a database controlled by a third party. Fig. 5 shows data structures that are used in the invention for storing annotated data information. The data structures store information about the location and/or shape of objects identified in video frames and information that enable viewer interactions with identified objects.

In particular, Fig. 5 shows a frame of video 200 that includes an image of a shirt 205 as a first object, an image of a hat 206 as a second object, and an image of a pair of shorts 207 as a third object. To represent the shape and/or location of these objects, the authoring tool 24 generates a mask 210 which is a two-dimensional pixel array where each pixel has an associated integer value independent of the pixels' color or intensity value. The mask represents the location information in various ways including by outlining or highlighting the object (or region of the display), by changing or enhancing a visual effect with which the object (or region) is

- 26 -

displayed, by placing a graphics in a fixed relation to the object or by placing a number in a fixed relation to the object. In this illustrative embodiment, the system generates a single mask 210 for each frame or video image. A collection of video images sharing common elements and a common camera perspective is defined as a shot. In the illustrative mask 210, there are four  
5 identified regions: a background region 212 identified by the integer 0, a shirt region 213 identified by the integer 1, a hat region 214 identified by the integer 2, and a shorts region 215 identified by the integer 3. Those skilled in the art will recognize that alternative forms of representing objects could equally well be used, such as mathematical descriptions of an outline of the image. The mask 210 has associated with it a unique identifier (UID) 216, a timestamp  
10 218, and a visibility word 219. The UID 216 refers to an object mapping table 217 associated with the particular mask. The timestamp 218 comes from the video encoder 36 and is used by the system to synchronize the masks with the video frames. This synchronization process is described in more detail below with respect to Fig. 6. The visibility word 219 is used by the system to identify those objects in a particular shot that are visible in a particular video frame.  
15 Although not shown in Fig. 5, all the other data structures of the system also include an in-use bit as described above.

The illustrative set of data structures shown in Fig. 5 that enable viewer interactions with identified objects include: object mapping table 217; object properties tables 220, 220'; primary dialog table 230; dialog tables 250, 250', 250''; selectors 290, 290', 290'', action identifiers 257, 257', 257'';  
20 257'', 257'''; style sheet 240; and strings 235, 235', 235'', 235''', 256, 256', 256'', 259, 259', 259'', 259''', 259'''', 292, 292', 292'', 292'''.

The object mapping table 217 includes a region number for each of the identified regions 212, 213, 214, 215 in the mask 210 and a corresponding UID 216 for each region of interest. For example, in the object mapping table 217, the shirt region 213 is stored as the integer value "one" and has associated the UID 01234. The UID 01234 points to the object properties table 220.  
25

Also in object mapping table 217, the hat region 214 is stored as the integer value two and has associated the UID 10324. The UID 10324 points to the object properties table 220'. The object mapping table begins with the integer one because the default value for the background is zero.

In general, object properties tables store references to the information about a particular object that is used by the system to facilitate viewer interactions with that object. For example, the object properties table 220 includes a title field 221 with the UID 5678, a price field 222 with the UID 910112, and a primary dialog field 223 with the UID 13141516. The second object properties table 220' includes a title field 221' with the UID 232323, a primary dialog field 223' with the same UID as the primary dialog field 223, and a price field 222' with the UID 910113. The UIDs of the title field 221 and the price field 222 of object properties table 220 point respectively to strings 235, 235' that contain information about the name of the shirt, "crew polo shirt," and its price, "\$14.95." The title field 221' of object properties table 220' points the string 235'' that contains information about name of the hat, "Sport Cap." The price field of object properties table 220' points to the string 235'''. Those skilled in the art will readily recognize that for a given section of authored video numerous object properties tables will exist corresponding to the objects identified by the authoring tool 24.

The UID of the primary dialog field 223 of object properties table 220 points to a primary dialog table 230. The dialog table 230 is also referenced by the UID of the primary dialog field 223' of the second object properties table 220'. Those skilled in the art will readily recognize that the second object properties table 220' corresponds to another object identified within the program containing the video frame 200. In general, dialog tables 230 structure the text and graphics boxes that are used by the system in interacting with the viewer. Dialog tables 230 act as the data model in a model-view-controller programming paradigm. The view seen by a viewer is described by a stylesheet table 240 with the UID 13579, and the controller component is supplied by software on the digital receiver 54. The illustrative primary dialog table 230 is



- 28 -

used to initiate interaction with a viewer. Additional examples of dialog tables include boxes for indicating to the colors 250 or sizes 250' that available for a particular item, the number of items he or she would like to purchase, for confirming a purchase 250'', and for thanking a viewer for his or her purchase. Those skilled in the art will be aware that this list is not exhaustive and that  
5 the range of possible dialog tables is extensive.

The look and feel of a particular dialog table displayed on the viewer's screen is controlled by a stylesheet. The stylesheet controls the view parameters in the model-view – controller programming paradigm, a software development paradigm well-known to those skilled in the art. The stylesheet field 232 of dialog table 230 contains a UID 13579 that points to  
10 the stylesheet table 240. The stylesheet table 240 includes a font field 241, a shape field 242, and graphics field 243. In operation, each of these fields have a UID that points to the appropriate data structure resource. The font field 241 points to a font object, the shape field 242 points to an integer, and the graphics field 243 points to an image object, discussed below. By having different stylesheets, the present system is easily able to tailor the presentation of  
15 information to a particular program. For example, a retailer wishing to advertise a shirt on two programs targeted to different demographic audiences would only need to enter the product information once. The viewer interactions supported by these programs would reference the same data except that different stylesheets would be used.

The name-UID pair organization of many of the data structures of the current  
20 embodiment provides compatibility advantages to the system. In particular, by using name-UID pairs rather than fixed fields, the data types and protocols can be extended without affecting older digital receiver software and allows multiple uses of the same annotated television program.

The flexibility of the current inventive system is enhanced by the system's requirement  
25 that the UIDs be globally unique. In the illustrative embodiment, the UIDs are defined as

numbers where the first set of bits represents a particular database license and the second set of bits represents a particular data structure element. Those skilled in the art will recognize that this is a particular embodiment and that multiple ways exist to ensure that the UIDs are globally unique.

5           The global uniqueness of the UIDs has the advantage that, for example, two broadcast networks broadcasting on the same cable system can be certain that the items identified in their programs can be distinguished. It also means that the headend receiver 50 is able to retrieve data from databases 30, 33 over the network 31 for a particular object because that object has an identifier that is unique across all components of the system. While the global nature of the  
10       UIDs means that the system can ensure that different objects are distinguishable, it also means that users of the current inventive system can choose not to distinguish items when such operation is more efficient. For example, a seller selling the same shirt on multiple programs only needs to enter the relevant object data once, and, further, the seller can use the UID and referenced data with its supplier thereby eliminating additional data entry overhead.

15           In the present embodiment of the current system, there are four defined classes of UIDs: null UIDs; resource UIDs; non-resource UIDs; and extended UIDs. The null UID is a particular value used by the system to indicate that the UID does not point to any resource. Resource UIDs can identify nine distinct types of resources: object mapping tables; object property tables; dialog tables; selectors; stylesheets; images; fonts; strings; and vectors. Selector data structures and  
20       vector resources are discussed below. Image resources reference graphics used by the system. The non-resource UIDs include four kinds of values: color values; action identifiers; integer values; and symbols. The action identifiers include "save/bookmark," "cancel," "next item," "previous item," "submit order," and "exit," among other actions that are taken by the viewer. Symbols can represent names in a name-UID pair; the system looks up the name in the stack and  
25       substitutes the associated UID. Non-resource UIDs contain a literal value. Extended UIDs

- 30 -

provide a mechanism by which the system is able increase the size of a UID. An extended UID indicates to the system that the current UID is the prefix of a longer UID.

When the system requires an input from the viewer it employs a selector 290 data structure. The selector 290 data structure is a table of pairs of UIDs where a first column  
5 includes UIDs of items to be displayed to the viewer and a second column includes UIDs of actions associated with each item. When software in the digital receiver 54 encounters a selector 290 data structure it renders on the viewer's screen all of the items in the first column, generally choices to be made by the viewer. These items could be strings, images, or any combination of non-resource UIDs. Once on the screen, the viewer is able to scroll up and down through the  
10 items. If the viewer chooses one of the items, the software in the digital receiver 54 performs the action associated with that item. These actions include rendering a dialog box, performing a non-resource action identifier, or rendering another selector 290' data structure. Selectors are referenced by menu1 fields 253, 253', 253'', 253'''.

In operation, when a viewer selects an object and navigates through a series of data  
15 structures, the system places each successive data structure used to display information to a viewer on a stack in the memory 128. For example consider the following viewer interaction supported by the data structures shown in Fig. 5. First a viewer selects the hat 214 causing the system to locate the object properties table 220' via the object mapping table 217 and to place the object properties table 220' on the stack. It is implicit in the following discussion that each  
20 data structure referenced by the viewer is placed on the stack.

Next the system displays a primary dialog table that includes the title 235'' and price 235'' of the hat and where the style of the information presented to the viewer is controlled by the stylesheet 240. In addition the initial display to the viewer includes a series of choices that are rendered based on the information contained in the selector 290. Based on the selector 290,  
25 the system presents the viewer with the choices represented by the strings "Exit" 256, "Buy"

256', and "Save" 256' each of which is respectively referenced by the UIDs 9999, 8888, and 7777. The action identifiers Exit 257' and Save 257 are referenced to the system by the UIDs 1012 and 1020 respectively.

When the viewer selects the "Buy" string 256', the system uses the dialog table 250, 5 UID 1011, to display the color options to the viewer. In particular, the selector 290' directs the system to display to the viewer the strings "Red" 292, "Blue" 292', "Green" 292'', and "Yellow" 292''', UIDs 1111, 2222, 3333, 4444 respectively. The title for the dialog table 250 is located by the system through the variable Symbol1 266. When the object properties table 220' was placed on the stack, the Symbol1 266 was associated with the UID 2001. Therefore, when the system 10 encounters the Symbol1 266' it traces up through the stack until it locates the Symbol1 266 which in turn directs the system to display the string "Pick Color " 259 via the UID 2001.

When the viewer selects the "Blue" 2222 string 292', the system executes the action identifier associated with the UID 5555 and displays a dialog table labeled by the string "Pick Size" 259 located through Symbol2, UID 2002. Based on the selector 290'' located by the UID 15 2004, the system renders the string "Large" 259'', UID 1122, as the only size available. If the viewer had selected another color, he would have been directed to the same dialog table, UID 5555, as the hat is only available in large. After the viewer selects the string "Large" 259'', the systems presents the viewer with the dialog table 250'', UID 6666, to confirm the purchase. The dialog table 250'' use the selector 290'', UID 2003, to present to the viewer the strings "Yes" and 20 "No", UIDs 1113 and 1114 respectively. After the viewer selects the "Yes" string 259'', the system transmits the transaction as directed by the action identifier submit order 257'', UID 1013. Had the viewer chosen the "No" strong 259'' in response to the confirmation request, the system would have exited the particular viewer interaction by executing the action identifier exit 257'. As part of the exit operation, the system would have dumped from the stack the object 25 properties table 220' and all of the subsequent data structures placed on the stack based on this

- 32 -

particular interaction with the system by the viewer. Similarly, after the execution of the purchase request by the system, it would have dumped the data structures from the stack.

If an action requires more than one step, the system employs a vector resource which is an ordered set of UIDs. For example, if a viewer wishes to save a reference to an item that he or she has located, the system has to perform two operations: first it must perform the actual save operation indicated by the non-resource save UID and second it must present the viewer with a dialog box indicating that the item has been saved. Therefore the vector UID that is capable of saving a reference would include the non-resource save UID and a dialog table UID that points to a dialog table referencing the appropriate text.

A particular advantage of the current inventive system is that the data structures are designed to be operationally efficient and flexible. For example, the distributed nature of the data structures means that only a minimum amount of data needs to be transmitted. Multiple data structure elements, for example the object properties tables 220, 220', can point to the same data structure element, for example the dialog table 230, and this data structure element only needs to be transmitted once. The stack operation described functions in concert with the distributed nature of the data structure in that, for example, the hat 214 does not have its own selector 290 but the selector 290 can still be particularized to the hat 214 when displayed. The distributed nature of the data structures also has the advantage that individual pieces of data can be independently modified without disturbing the information stored in the other data structures.

Another aspect of the current inventive system that provides flexibility is an additional use of symbols as a variable datatype. In addition to having a value supplied by a reference on the stack, a symbol can reference a resource that can be supplied at some time after the initial authoring process. For example, a symbol can direct the DTV Broadcast Infrastructure 12 to supply a price at broadcast time. This allows, for example, a seller to price an object differently depending on the particular transmitting cable system.

A further aspect of the flexibility provided by the distributed data structure of the current invention is that it supports multiple viewer interaction paradigms. For example, the extensive variation in dialog tables and the ordering of their linkage means that the structure of the viewer's interaction is malleable and easily controlled by the author.

5        Another example of the variation in a viewer's experience supported by the system is its ability to switch between multiple video streams. This feature exploits the structure of a MPEG2 transport stream which is made up of multiple program streams, where each program stream can consist of video, audio and data information. In a MPEG2 transport stream, a single transmission at a particular frequency can yield multiple digital television programs in parallel.

10    As those skilled in the art would be aware, this is achieved by associating a program mapping table, referred to as a PMT, with each program in the stream. The PMT identifies the packet identifiers (PIDs) of the packets in the stream that correspond to the particular program. These packets include the video, audio, and data packets for each program.

Referring to Figure 5A, there is shown an object properties table 220'' containing a link

15    type field 270 having a corresponding link type entry in the UID field and a stream\_num field 227 with a corresponding PID 228. To enable video stream switching, the authoring tool 24 selects the PID 228 corresponding to the PID of a PMT 229 of a particular program stream.

When the object corresponding to the object properties table 220'' is selected, the digital receiver

54 uses the video link entry 271 of the link type field 270 to determine that the object is a video

20    link object. The digital receiver 54 then replaces the PID of the then current PMT with the PID 228 of the PMT 229. The digital receiver 54 subsequently uses the PMT 229 to extract data corresponding to the new program. In particular the program referred to by the PMT 229 includes a video stream 260 identified by PID17, two audio streams 261, 262 identified by PID18 and PID19, and a private data stream 263 identified by PID20. In this way the viewer is

- 34 -

able to switch between different program streams by selecting the objects associated with those streams.

Fig. 6 is a flow diagram 500 of the data flow and flow control of an embodiment of the system shown in Fig. 2. Fig. 6 shows sequences of steps that occur when a viewer interacts with the hardware and software of the system. In Fig. 6, a stream 502 of data for masks is decoded at a mask decoder 504. The decoded mask information 506 is placed into a buffer or queue as masks 508, 508', 508''. In parallel with the mask information 506, a stream 510 of events, which may be thought of as interrupts, are placed in an event queue as events 512, 512', 512'', where an event 512 corresponds to a mask 508 in a one-to-one correspondence. A thread called mask 514 operates on the masks 508. The mask 514 thread locates the mask header, assembles one or more buffers, and handles the mask information in the queue to generate mask overlays.

In order to display mask information, a thread called decompress 528 decodes and expands a mask, maintained for example in (320 by 240) pixel resolution, to appropriate size for display on a video screen 530, for example using (640 by 480) pixel resolution. The decompress thread 528 synchronizes the display of mask overlays to the video by examining a timestamp that is encoded in the mask information and comparing it to the timestamp of the current video frame. If the mask overlay frame is ahead of the video frame, the decompress thread sleeps for a calculated amount of time representing the difference between the video and mask timestamps. This mechanism keeps the masks in exact synchronization with the video so that masks appear to overlay video objects.

A second stream 516 of data for annotations is provided for a second software thread called objects 518. The objects data stream 516 is analyzed and decoded by the objects 518 thread, which decodes each object and incorporates it into the object hierarchy. The output of the objects 518 thread is a stream of objects 519 that have varying characteristics, such as shape, size, and the like.

A thread called model 520 combines the masks 508 and the objects 519 to form a model of the system. The mask information includes a unique ID for every object that is represented in the mask overlay. The unique IDs correspond to objects that are stored in the model. The model 520 thread uses these unique IDs to synchronize, or match, the corresponding information.

5       The model 520 thread includes such housekeeping structures as a stack, a hash table, and a queue, all of which are well known to those of ordinary skill in the software arts. For example, the stack can be used to retain in memory a temporary indication of a state that can be reinstituted or a memory location that can be recalled. A hash table can be used to store data of a particular type, or pointers to the data. A queue can be used to store a sequence of bits, bytes,  
10   data or the like. The model 520 interacts with a thread called view 526 that controls the information that is displayed on a screen 530 such as a television screen. The view 526 thread uses the information contained in the model 520 thread, which keeps track of the information needed to display a particular image, with or without interactive content. The view 526 thread also interacts with the mask 514 thread, to insure that the proper information is made available to  
15   the display screen 530 at the correct time.

A thread called soft 522 controls the functions of a state machine called state 524. The details of state 524 are discussed more fully with regard to Fig. 7. State 524 interacts with the thread view 526.

A garbage collector 532 is provided to collect and dispose of data and other information  
20   that becomes outdated, for example data that has a timestamp for latest use that corresponds to a time that has already passed. The garbage collector 532 can periodically sweep the memory of the system to remove such unnecessary data and information and to recover memory space for storing new data and information. Such garbage collector software is known in the software arts.

Fig. 7 depicts the interactions between and among states within the state machine state  
25   524. The state state machine 524 includes a reset 602 which, upon being activated, brings the



- 36 -

state state machine 524 to a refreshed start up condition, setting all adjustable values such as memory contents, stack pointers, and the like to default values, which can be stored for use as necessary in ROM, SDRAM, magnetic storage, CD-ROM, or in a protected region of memory. Once the system has been reset, the state of the state state machine 524 transitions to a condition  
5 called interactive content icon 604, as indicated by arrow 620. See Fig. 7.

Interactive content icon 604 is a state in which a visual image, similar to a logo, appears in a defined region of the television display 58. The visual image is referred to as an "icon," hence the name interactive content icon for a visual image that is active. The icon is capable of changing appearance or changing or enhancing a visual effect with which the icon is displayed,  
10 for example by changing color, changing transparency, changing luminosity, flashing or blinking, or appearing to move, or the like, when there is interactive information available.

The viewer of the system can respond to an indication that there is information by pressing a key on a hand-held device. For example, in one embodiment, pressing a right-pointing arrow or a left-pointing arrow (analogous to the arrows on a computer keyboard, or the  
15 volume buttons on a hand-held TV remote device) causes the state of the state state machine 524 to change from interactive content icon 604 to mask highlight (MH) 606. The state transition from interactive content icon 604 to MH 606 is indicated by the arrow 622.

In the state MH 606, if one or more regions of an image correspond to material that is available for presentation to the viewer, one such region is highlighted, for example by having a  
20 circumscribing line that outlines the region that appears on the video display (see Fig. 1D), or by having the region or a portion thereof change appearance. In one embodiment, if a shirt worn by a man is the object that is highlighted, a visually distinct outline of the shirt appears in response to the key press, or the shirt changes appearance in response to the key press. Repeating the key press, or pressing the other arrow key, causes another object, such as a wine bottle standing on a

table, to be highlighted in a similar manner. In general, the objects capable of being highlighted are successively highlighted by successive key presses.

If the viewer takes no action for a predetermined period of time, for example ten seconds, the state of the state machine 524 reverts to the interactive content icon 604 state, as denoted by the arrow 624. Alternatively, if the viewer activates a button other than a sideways-pointing arrow, such as the "select" button which often appears in the center of navigational arrows on remote controls, the state proceeds from the state MH 606 to a state called info box 608. Info box 608 is a condition wherein information appears in a pop-up box (i.e., an information box). The state transition from MH 606 to info box 608 is indicated by the arrow 626. The information that appears is specified by an advertiser or promoter of the information, and can, for example, include the brand name, model, price, local vendor, and specifications of the object that is highlighted. As an example, in the case of the man's shirt, the information might include the brand of shirt, the price, the range of sizes that are available, examples of the colors that are available, information about one or more vendors, information about special sale offers, information about telephone numbers or email addresses to contact to place an order, and the like.

There are many possible responses that a viewer might make, and these responses lead, via multiple paths, back to the state interactive content icon 604, as indicated generally by the arrow 628. The responses can, for example, include the viewer expressing an indication of interest in the information provided, as by making a purchase of the item described, inquiring about additional information, or by declining to make such a purchase.

While the system is in the interactive content icon 604 state, the viewer can press a burst button, which activates a state called burst 610, causing a transition 630 from interactive content icon 604 to burst 610. In the burst 610 state, the video display automatically highlights in succession all of the objects that currently have associated information that can be presented to a

- 38 -

viewer. The highlight period of any one object is brief, of the order of 0.03 to 5 seconds, so that the viewer can assess in a short time which objects may have associated information for presentation. A preferred highlight period is in the range of 0.1 to 0.5 seconds. The burst 610 state is analogous to a scan state for scanning radio receivers, in which signals that can be  
5 received at a suitable signal strength are successively tuned in for brief times.

The burst 610 state automatically reverts 632 to the interactive content icon 604 state once the various objects that have associated information have been highlighted. Once the system has returned to the interactive content icon 604 state, the viewer is free to activate an object of interest that has associated information, as described above.

10 In another embodiment, the burst 610 state can be invoked by a command embedded within a communication. In yet another embodiment, the burst 610 state can be invoked periodically to inform a viewer of the regions that can be active, or the burst 610 state can be invoked when a new shot begins that includes regions that have set visibility bits.

The interactive content icon can be used to provide visual clues to a viewer. In one  
15 embodiment, the interactive content icon appears only when there is material for display to the viewer in connection with one or more regions of an image.

In one embodiment, the interactive content icon is active when the burst 610 state is invoked. The interactive content icon can take on a shape that signals that the burst 610 state is beginning, for example, by displaying the interactive content icon itself in enhanced visual  
20 effect, similar in appearance to the enhanced visual effect that each visible region assumes. In different embodiments, an enhanced visual effect can be a change in color, a change in luminosity, a change in the icon itself, a blinking or flashing of a region of a display, or the like.

In one embodiment, the interactive content icon is augmented with additional regions, which may be shaped like pointers to points on the compass or like keys of the digital receiver  
25 remote control. The augmented regions are displayed, either simultaneously or successively,

- 39 -

with an enhanced visual effect. An illustrative example of various embodiments are depicted schematically in Figs. 8A through 8G. Fig. 8A depicts an inactive interactive content icon. Fig. 8B depicts an active interactive content icon, that is visually enhanced. Fig. 8C depicts a interactive content icon entering the burst state, in which four arrowheads are added pointing to the compass positions North (N), East (E), South (S) and West (W). For example, the augmented regions can be presented in forms that are reminiscent of the shapes of the buttons on a handheld device. In one embodiment, the North (N) and South (S) arrowheads can correspond to buttons that change channels on a video handheld remote, and the East (E) and West (W) arrowheads can correspond to buttons that change volume on a video handheld remote, so as to remind the viewer that pushing those buttons will invoke a burst state response.

Fig. 8D depicts a interactive content icon in the active burst state, in which the interactive content icon itself and the arrowhead pointing to the compass position North (N) are displayed with enhanced visual effects. Fig. 8E depicts a interactive content icon in the active burst state, in which the interactive content icon itself and the arrowhead pointing to the compass position East (E) are displayed with enhanced visual effects. Fig. 8F depicts a interactive content icon in the active burst state, in which the interactive content icon itself and the arrowhead pointing to the compass position South (S) are displayed with enhanced visual effects. Fig. 8G depicts a interactive content icon in the active burst state, in which the interactive content icon itself and the arrowhead pointing to the compass position West (W) are displayed with enhanced visual effects.

As discussed earlier, the information that appears on the video display 58, including the television program and any annotation information that may be made available, is transmitted from a headend 50 to the digital receiver 54. Video images generally contain much information. In modern high definition television formats, a single video frame may include more than 1000 lines. Each line can comprise more than 1000 pixels. In some formats, a 24-bit integer is

- 40 -

required for the representation of each pixel. The transmission of such large amounts of information is burdensome. Compression methods that can reduce the amount of data that needs to be transmitted play a useful role in television communication technology. Compression of data files in general is well known in the computer arts. However, new forms of file  
5 compression are used in the invention, which are of particular use in the field of image compression.

One traditional compression process is called "run-length encoding." In this process, each pixel or group of identical pixels that appear in succession in a video line is encoded as an ordered pair comprising a first number that indicates how many identical pixels are to be  
10 rendered and a second number that defines the appearance of each such identical pixel. If there are long runs of identical pixels, such a coding process can reduce the total number of bits that must be transmitted. However, in pathological instances, for example where every pixel differs from the pixel that precedes it and the pixel that follows it, the coding scheme can actually require more bits than the number of bits required to represent the pixel sequence itself.

15 In one embodiment, an improvement on run-length encoding, called "Section Run-Length Encoding," is obtained if two or more successive lines can be categorized as having the same sequence of run lengths with the same sequence of appearance or color. The two or more lines are treated as a section of the video image. An example of such a section is a person viewed against a monochrome background. A transmitter encodes the section by providing a  
20 single sequence of colors that is valid for all lines in the section, and then encodes the numbers of pixels per line that have each successive color. This method obviates the repeated transmission of redundant color information which requires a lengthy bit pattern per color.

Fig. 9A depicts an image 700 of a person 705 shown against a monochrome background 710, for example, a blue background. Fig. 9A illustrates several embodiments of compression  
25 methods for video images. In Fig. 9A the person has a skin color which is apparent in the region

720. The person is wearing a purple shirt 730 and green pants 740. Different colors or appearances can be encoded as numbers having small values, if the encoder and the decoder use a look-up table to translate the coded numbers to full (e.g., 24-bit) display values. As one embodiment, a background color may be defined, for the purposes of a mask, as a null, or a transparent visual effect, permitting the original visual appearance of the image to be displayed without modification.

In this embodiment of "Section Run-Length Encoding," the encoder scans each row 752, 754, 762, 764, and records the color value and length of each run. If the number of runs and the sequence of colors of the first row 752 of a video frame does not match that of the succeeding row 754, the first row 752 is encoded as being a section of length 1, and the succeeding row 754 is compared to the next succeeding row. When two or more rows do contain the same sequence of colors, the section is encoded as a number of rows having the same sequence of colors, followed by a series of ordered pairs representing the colors and run lengths for the first row of the section. As shown in Fig. 9B for an example having three rows, the first row includes (n) values of pairs of colors and run lengths. The remaining two rows are encoded as run lengths only, and the colors used in the first row of the section are used by a decoder to regenerate the information for displaying the later rows of the section. In one embodiment, the section can be defined to be less than the entire extent of a video line or row.

As an example expressed with regard to Fig. 9A, the illustrative rows 752 and 754, corresponding to video scan lines that include the background 710, a segment of the person's skin 720, and additional background 710. The illustrative rows 752 and 754 both comprise runs of blue pixels, skin-colored pixels, and more blue pixels. Thus, the rows 752 and 754, as well as other adjacent rows that intersect the skin-colored head or neck portion of the person, would be encoded as follows: a number indicating exactly how many rows similar to the lines 752, 754 are in a section defined by the blue background color-skin color-blue background color pattern; a

- 42 -

first row encoding comprising the value indicative of blue background color and an associated pixel count, the value indicative of skin color 720 and an associated pixel count, and the value indicative of blue background color and another associated pixel count. The remaining rows in the section would be encoded as a number representing a count of blue background color pixels, a number representative of a count of pixels to be rendered in skin color 720, and a number representing the remaining blue background color pixels.

In another embodiment, a process that reduces the information that needs to be encoded, called "X-Run-Length Encoding," involves encoding only the information within objects that have been identified. In this embodiment, the encoded pixels are only those that appear within the defined object, or within an outline of the object. An encoder in a transmitter represents the pixels as an ordered triple comprising a value, a run length and an offset defining the starting position of the run with respect to a known pixel, such as the start of the line. In a receiver, a decoder recovers the encoded information by reading the ordered triple and rendering the pixels according to the encoded information.

Referring again to Fig. 9A, each of the illustrative lines 752 and 754 are represented in the X-Run-Length Encoding process as an ordered triple of numbers, comprising a number indicative of the skin color 720, a number representing how many pixels should be rendered in skin color 720, and a number indicative of the distance from one edge 712 of the image 700 that the pixels being rendered in skin color 720 should be positioned. An illustrative example is given in Fig. 9C.

In yet another embodiment, a process called "X-Section-Run-Length Encoding," that combines features of the Section Run-Length and X-Run-Length encoding processes is employed. The X-Section-Run-Length Encoding process uses color values and run lengths as coding parameters, but ignores the encoding of background. Each entry in this encoding scheme is an ordered triple of color, run length, and offset values as in X-Run-Length Encoding.

The illustrative lines 762 and 764 are part of a section of successive lines that can be described as follows: the illustrative lines 762, 764 include, in order, segments of blue background 710, an arm of purple shirt 730, blue background 710, the body of purple shirt 730, blue background 710, the other arm of purple shirt 730, and a final segment of blue background.

5 Illustrative lines 762, 764 and the other adjacent lines that have the same pattern of colors are encoded as follows: an integer defining the number of lines in the section; the first line is encoded as three triples of numbers indicating a color, a run length and an offset; and the remaining lines in the section are encoded as three ordered doubles of numbers indicating a run length and an offset. The color values are decoded from the sets of triples, and are used  
10 thereafter for the remaining lines of the section. Pixels which are not defined by the ordered doubles or triples are rendered in the background color. An illustrative example is shown in Fig. 9D, using three rows.

A still further embodiment involves a process called "Super-Run-Length Encoding." In this embodiment, a video image is decomposed by a CPU into a plurality of regions, which can  
15 include sections. The CPU applies the compression processes described above to the various regions, and determines an encoding of the most efficient compression process on a section-by-section basis. The CPU then encodes the image on a section-by-section basis, as a composite of the most efficient processes, with the addition of a prepended integer or symbol that indicates the process by which each section has been encoded. An illustrative example of this Super-Run-  
20 Length Encoding is the encoding of the image 700 using a combination of run length encoding for some lines of the image 700, X Run-Length Encoding for other lines (e.g., 752, 754) of image 700, X-Section-Run-Length Encoding for still other lines (e.g., 762, 764) of image 700, and so forth.

Other embodiments of encoding schemes may be employed. One embodiment that may  
25 be employed involves computing an offset of the pixels of one line from the preceding line, for



- 44 -

example shifting a subsequent line, such as one in the vicinity of the neck of the person depicted in FIG. 9A, by a small number of pixels, and filling any undefined pixels at either end of the shifted line with pixels representing the background. This approach can be applied to both run lengths and row position information. This embodiment provides an advantage that an offset of  
5 seven or fewer pixels can be represented as a signed four-bit value, with a large savings in the amount of information that needs to be transmitted to define the line so encoded. Many images of objects involve line to line offsets that are relatively modest, and such encoding can provide a significant reduction in data to be transmitted.

Another embodiment involves encoding run values within the confines of an outline as  
10 ordered pairs, beginning at one edge of the outline. Other combinations of such encoding schemes will be apparent to those skilled in the data compression arts.

In order to carry out the objectives of the invention, an ability to perform analysis of the content of images is useful in addition to representing the content of images efficiently. Television images comprising a plurality of pixels can be analyzed to determine the presence or  
15 absence of persons, objects and features, so that annotations can be assigned to selected persons, objects and features. The motions of persons, objects and features can also be analyzed. An assignment of pixels in an image or a frame to one or more persons, objects, and/or features is carried out before such analysis is performed.

The analysis is useful in manipulating images to produce a smooth image, or one which  
20 is pleasing to the observer, rather than an image that has jagged or rough edges. The analysis can also be used to define a region of the image that is circumscribed by an outline having a defined thickness in pixels. In addition, the ability to define a region using mathematical relationships makes possible the visual modification of such a region by use of a visibility bit that indicates whether the region is visible or invisible, and by use of techniques that allow the  
25 rendering of all the pixels in a region in a specific color or visual effect. An image is examined

- 45 -

for regions that define matter that is of interest. For example, in Fig. 9A, a shirt region 730, a head region 720, and a pants region 740 are identified.

In one embodiment, the pixels in an image or frame are classified as belonging to a region. The classification can be based on the observations of a viewer, who can interact with an image presented in digital form on a digital display device, such as the monitor of a computer. In one embodiment, the author/annotator can mark regions of an image using an input device such as a mouse or other computer pointing device, a touch screen, a light pen, or the like. In another embodiment, the regions can be determined by a computing device such as a digital computer or a digital signal processor, in conjunction with software. In either instance, there can be pixels that are difficult to classify as belonging to a region, for example when a plurality of regions abut one another.

In one embodiment, a pixel that is difficult to classify, or whose classification is ambiguous, can be classified by a process that involves several steps. First, the classification of the pixel is eliminated, or canceled. This declassified pixel is used as the point of origin of a classification shape that extends to cover a plurality of pixels (i.e., a neighborhood) in the vicinity of the declassified pixel. The pixels so covered are examined for their classification, and the ambiguous pixel is assigned to the class having the largest representation in the neighborhood. In one embodiment, the neighborhood comprises next nearest neighbors of the ambiguous pixel. In one embodiment, a rule is applied to make an assignment in the case of ties in representation. In one embodiment, the rule can be to assign the class of a pixel in a particular position relative to the pixel, such as the class of the nearest neighbor closest to the upper left hand corner of the image belonging to a most heavily represented class.

In another embodiment, a pixel that is difficult to classify, or whose classification is ambiguous, can be classified by a process which features a novel implementation of principles of mathematical morphology. Mathematical morphology represents the pixels of an image in

- 46 -

mathematical terms, and allows the algorithmic computation of properties and transformations of images, for example, using a digital computer or digital signal processor and appropriate software. The principles of mathematical morphology can be used to create various image processing applications. A very brief discussion of some of the principles will be presented here.

5 In particular, the methods known as dilation and erosion will be described and explained. In general, dilation and erosion can be used to change the shape, the size and some features of regions. In addition, some illustrative examples of applications of the principles of mathematical morphology to image processing will be described.

Dilation and erosion are fundamental mathematical operations that act on sets of pixels.

10 As an exemplary description in terms of an image in two-dimensional space, consider the set of points of a region  $R$ , and a two-dimensional morphological mask  $M$ . The illustrative discussion, presented in terms of binary mathematical morphology, is given with respect to Figs. 10A and 10B. In Fig. 10A, the morphological mask  $M$  has a shape, for example, a five pixel array in the shape of a "plus" sign. Morphological masks of different shape can be selected depending on the  
15 effect that one wants to obtain. The region  $R$  can be any shape; for purposes of illustration, the region  $R$  will be taken to be the irregular shape shown in Fig. 10A.

The morphological mask  $M$  moves across the image in Fig. 10A, and the result of the operation is recorded in an array, which can be represented visually as a frame as shown in Fig. 10 B. For the illustrative morphological mask, the pixel located at the intersection of the vertical  
20 and the horizontal lines of the "plus" sign is selected as a "test" pixel, or the pixel that will be "turned on" (e.g., set to 1) or "turned off" (e.g., set to 0) according to the outcome of the operation applied.

For binary erosion, the mathematical rule, expressed in terms of set theory, can be that the intersection of one or more pixels of the morphological mask  $M$  with the region  $R$  defines the  
25 condition of the pixel to be stored in an array or to be plotted at the position in Fig. 10B

corresponding to the location of the test pixel in Fig. 10A. This rule means that, moving the morphological mask one pixel at a time, if all the designated pixel or pixels of the morphological mask  $M$  intersect pixels of the region  $R$ , the test pixel is turned on and the corresponding pixel in Fig. 10B is left in a turned on condition. The scanning of the mask can be from left to right

5 across each row of the image, starting at the top row and moving to the bottom, for example.

Other scan paths that cover the entire image (or at least the region of interest) can be used, as will be appreciated by those of ordinary skill in the mathematical morphology arts. This operation tends to smooth a region, and depending on the size and shape of the morphological mask, can have a tendency to eliminate spiked projections along the contours of a region.

10 Furthermore, depending on the size and shape of the morphological mask, an image can be diminished in size.

Binary dilation can have as a mathematical rule, expressed in terms of set theory, that the union of the morphological mask  $M$  with the region  $R$  defines the condition of the pixel to be plotted at the position in Fig. 10B corresponding to the location of the test pixel in Fig. 10A. For

15 a given location of the morphological mask  $M$ , the pixels of  $R$  and the pixels of  $M$  are examined, and if any pixel turned on in  $M$  corresponds to a pixel turned on in  $R$ , the test pixel is turned on. This rule is also applied by scanning the morphological mask across the image as described above, for example, from left to right across each row of the image, again from the top row to the bottom. This operation can have a tendency to cause a region to expand and fill small holes.

20 The operations of dilation and erosion are not commutative, which means that in general, one obtains different results for applying erosion followed by dilation as compared to applying dilation followed by erosion.

The operations of erosion and dilation, and other operations based upon these fundamental operations, can be applied to sets of pixels defined in space, as are found in a two-

25 dimensional image, as has just been explained. The same operations can be applied equally well

- 48 -

for sets of pixels in a time sequence of images, as is shown in Figs. 11A and 11B. In Fig. 11A, time may be viewed as a third dimension, which is orthogonal to the two dimensions that define each image or frame. Fig. 11A shows three images or frames, denoted as N-1, N, and N+1, where frame N-1 is displayed first, frame N appears next, and finally frame N+1 appears. Each frame can be thought of as having an x-axis and a y-axis. In an illustrative example, each frame comprises 480 horizontal rows of 640 pixels, or columns each. It is conventional to number rows from the top down, and to number columns from the left edge and proceed to the right. The upper left hand corner is row 0, column 0, or (0,0). The x-axis defines the row, with increasing x value as one moves downward along the left side of the frame, and the y-axis defines the column number per row, with increasing y value as one moves rightward along the top edge of the frame. The time axis, along which time increases, is then viewed as proceeding horizontally from left to right in Fig. 11A.

The operations of erosion and dilation in two-dimensional space used a morphological mask, such as the five-pixel "plus" sign, which is oriented in the plane of the image or frame.

An operation in the time dimension that uses the two-dimensional five-pixel "plus" sign as a morphological mask can be understood as in the discussion that follows, recognizing that one dimension of the "plus" sign lies along the time axis, and the other lies along a spatial axis. In other embodiments, one could use a one dimensional morphological mask along only the time axis, or a three-dimensional morphological mask having dimensions in two non-collinear spatial directions and one dimension along the time axis.

Let the "test" pixel of the two-dimensional five-pixel "plus" sign morphological mask be situated at row r, column c, or location (r,c), of frame N in Fig. 11A. The pixels in the vertical line of the "plus" sign is at column c of row r-1 (the row above row r) of frame N and column c of row r+1 (the row below row r) of frame N. The pixel to the "left" of the "test" pixel is at row r, column c of frame N-1 of Fig. 11A (the frame preceding frame N), and the pixel to the "right"

of the "test" pixel is at row  $r$ , column  $c$  of frame  $N+1$  of Fig. 11A (the frame following frame  $N$ ).

An operation using this morphological mask thus has its result recorded visually at row  $r$ , column  $c$  of a frame corresponding to frame  $N$ , and the result can be recorded in an array at the corresponding location. However, in this example, the computation depends on three pixels  
5 situated in frame  $N$ , one pixel situated in frame  $N-1$ , and one situated in frame  $N+1$ . Fig. 11A schematically depicts the use of the five-pixel "plus" mask on three images or frames that represent successive images in time, and Fig. 11B depicts the result of the computation in a frame corresponding to frame  $N$ .

In this inventive system, a novel form of erosion and dilation is applied in which all  
10 regions are eroded and dilated in one pass, rather than working on a single region at a time (where the region is labeled '1' and the non-region is '0'), and repeating the process multiple times in the event that there are multiple regions to treat. In the case of erosion, if the input image contains  $R$  regions, the pixels of which are labeled 1, 2, ...  $r$ , respectively, then the test pixel is labeled, for example, '3', if and only if all the pixels under the set pixels in the  
15 morphological mask are labeled 3. Otherwise, the test pixel is assigned 0, or "unclassified." In the case of dilation, if the input image contains  $R$  regions, the pixels of which are labeled 1, 2, ...  $r$ , respectively, then the test pixel is labeled, for example, '3', if and only if the region with the greatest number of pixels is the one with label 3. Otherwise, the test pixel is assigned 0, or "unclassified."

20 Two dimensional floodfill is a technique well known in the art that causes a characteristic of a two-dimensional surface to be changed to a defined characteristic. For example, two-dimensional floodfill can be used to change the visual effect of a connected region of an image to change in a defined way, for example changing all the pixels of the region to red color. Three-dimensional floodfill can be used to change all the elements of a volume to a defined  
25 characteristic. For example, a volume can be used to represent a region that appears in a series

- 50 -

of sequential two-dimensional images that differ in sequence number or in time of display as the third dimension.

An efficient novel algorithm has been devised to floodfill a connected three-dimensional volume starting with an image that includes a region that is part of the volume. In overview, the method allows the selection of an element at a two-dimensional surface within the volume, and performs a two-dimensional floodfill on the region containing that selected element. The method selects a direction along the third dimension, determines if a successive surface contains an element within the volume, and if so, performs a two-dimensional floodfill of the region containing such an element. The method repeats the process until no further elements are found, and returns to the region first floodfilled and repeats the process while moving along the third dimension in the opposite direction.

An algorithmic image processing technique has been devised using a three-dimensional flood-fill operator in which the author selects a point within a group of incorrectly classified points. The selected point can be reclassified using a classification method as described earlier. The entire group of pixels contiguous with the selected point is then reclassified to the classification of the selected point. Pixels that neighbor the reclassified pixels in preceding and following frames can also be reclassified.

In one embodiment, the three-dimensional volume to be reclassified comprises two dimensions representing the image plane, and a third dimension representing time. In this embodiment, for every pixel (r, c) in frame N of Fig. 11A that has changed from color A to color B due to the two-dimensional floodfill operation in frame N, if pixel (r, c) in frame N+1 of Fig. 11A is currently assigned color A, then the two-dimensional floodfill is run starting at pixel (r, c) in frame N+1 of Fig. 11A, thereby changing all the contiguous pixels in frame N+1 assigned to color A. Again with reference to Fig. 11A, it is equally possible to begin such a process at frame N and proceed backward in the time dimension to frame N-1. In one embodiment, the three-

dimensional floodfill process is terminated at a frame in which no pixel has a label that requires changing as a result of the flood fill operation. In one embodiment, once three-dimensional floodfill is terminated going in one direction in time, the process is continued by beginning at the initial frame N and proceeding in the opposite direction in time until the process terminates again.

Fig. 11C is a flow diagram 1150 showing an illustrative process by which three-dimensional floodfill is accomplished, according to one embodiment of the invention. The process starts at the circle 1152 labeled "Begin." The entity that operates the process, such as an operator of an authoring tool, or alternatively, a computer that analyzes images to locate within images one or more regions corresponding to objects, selects a plurality of sequential two-dimensional sections that circumscribe the volume to be filled in the three-dimensional floodfill process, as indicated by step 1154. In one embodiment, the three-dimensional volume comprises two dimensional sections disposed orthogonally to a third dimension, each two-dimensional section containing locations identified by a first coordinate and a second coordinate. For example, in one embodiment, the two-dimensional sections can be image frames, and the third dimension can represent time or a frame number that identifies successive frames. In one embodiment, the first and second coordinates can represent row and column locations that define the location of a pixel within an image frame on a display.

In step 1156, the process operator defines a plurality of regions in at least one of the two-dimensional sections, each region comprising at least one location. From this point forward in the process, the process is carried out using a machine such as a computer that can perform a series of instructions such as may be encoded in software. The computer can record information corresponding to the definitions for later use, for example in a machine-readable memory. For example, in an image, an operator can define a background and an object of interest, such as shirt



- 52 -

In step 1158, the computer selects a first region in one of the two-dimensional sections, the region included within the volume to be filled with a selected symbol. In one embodiment, the symbol can be a visual effect when rendered on a display, such as a color, a highlighting, a change in luminosity, or the like, or it can be a character such as an alphanumeric character or another such symbol that can be rendered on a display.

In step 1160, the computer that runs the display fills the first region with the selected symbol. There are many different well-known graphics routines for filling a two-dimensional region with a symbol, such as turning a defined region of a display screen to a defined color. Any such well-known two-dimensional graphics routine can be implemented to carry out the two-dimensional filling step.

In step 1162, the computer moves in a first direction along the third dimension to the successive two-dimensional section. In one embodiment, the process operator moves to the image immediately before or after the first image selected, thus defining a direction in time, or in the image sequence.

In step 1164, the computer determines whether a location in the successive two-dimensional section corresponding to a filled location in the two-dimensional section of the previous two-dimensional section belongs to the volume. The process operator looks up information recorded in the definitions of the two dimensional regions accomplished in step 1156.

In step 1166, the computer makes a selection based on the outcome of the determination performed in step 1164. If there is a positive outcome of the determination step 1164, the computer fills a region that includes the location in the successive two-dimensional section with the selected symbol, as indicated at step 1168. As indicated at step 1170, beginning with the newly-filled region in the successive two-dimensional section, the computer repeats the moving

- 53 -

step 1162, the determining step 1164 and the filling step 1168 (that is, the steps recited immediately heretofore) until the determining step results in a negative outcome.

Upon a negative outcome of any determining step 1164 heretofore, the computer returns to the first region identified in step 1158 (which has already been filled), and, moving along the  
5 third dimension in a direction opposite to the first direction, repeating the steps of moving (e.g., a step similar to step 1162 but going on the opposite direction), determining (e.g., a step such as step 1164) and filling (e.g., a step such as step 1168) as stated above until a negative outcome results for a determining step. This sequence is indicated in summary form at step 1172. At step 1174, the process ends upon a negative outcome of a determining step.

10 Another application involves creating outlines of regions, for example to allow a region to be highlighted either in its entirety, or to be highlighted by changing the visual effect associated with the outline of the region, or some combination of the two effects. In one embodiment, a method to construct outlines from labeled regions is implemented as depicted in Figs. 12A – 12B. A region 1210 to be outlined having an outline 1215 in input image 1218 is  
15 shown in Fig. 12A. A square morphological mask 1220 having an odd number of pixels whose size is proportional to the desired outline thickness is passed over the region 1210. At every position in the input region 1210, the pixels falling within the morphological mask are checked to see if they are all the same. If so, a '0' is assigned to the test pixel in the output image 1230 of Fig. 12B. If a pixel is different from any other pixel within the morphological mask, then the  
20 label which falls under the morphological mask's center pixel is assigned to the test pixel in the output image 1230. As the morphological mask 1220 passes over the region 1210, a resulting outline 1215' is generated in output image 1230. In other embodiments, square morphological masks having even numbers of pixels, morphological masks having shapes other than square, and square morphological masks having odd numbers of pixels can be used in which one selects

- 54 -

a particular pixel within the morphological mask as the pixel corresponding to the test pixel 1222 in the output image 1230.

It will be understood that those of ordinary skill in using the principles of mathematical morphology may construct the foregoing examples of applications by use of alternative morphological masks, and alternative rules, and will recognize many other similar applications based on such principles.

In a series of related images, or a shot as described previously, such as a sequence of images showing a person sitting on a bench in the park, one or more of the selected objects may persist for a number of frames. In other situations, such as an abrupt change in the image, as where the scene changes to the view perceived by the person sitting on the park bench, some or all of the regions identified in the first scene or shot may be absent in the second scene or shot. The system and method of the invention can determine both that the scene has changed (e.g., a new shot begins) and that one or more regions present in the first scene are not present in the second scene.

In one embodiment, the system and method determines that the scene or shot has changed by computing a histogram of pixels that have changed from one image to a successive image and comparing the slope of the successive instances (or time evolution) of the histogram to a predefined slope value. FIG. 13 shows three illustrative examples of the evolutions of histograms over successive frames (or over time). The topmost curve 1310 has a small variation in slope from zero and represents motion at moderate speed. The middle curve 1320 shows a somewhat larger variation in slope and represents sudden motion. The lowermost curve 1330 shows a large variation in slope, and represents a shot change or scene change at frame F. If the slope of the histogram evolution plot exceeds a predetermined value, as does the lowermost curve 1330, the system determines that a shot change has occurred.

- 55 -

While the invention has been particularly shown and described with reference to specific preferred embodiments, it should be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

- 56 -

What is claimed is:

- 1 1. A method of analyzing elements of a three-dimensional array, comprising the steps of:
  - 2 (a) defining a subset of a three-dimensional array, said subset having a plurality of
  - 3 sequential two-dimensional arrays containing elements for analysis, wherein said
  - 4 elements within the two-dimensional arrays are represented by a first axis and a second
  - 5 axis, said first and second axes being two non-collinear axes and said third dimension
  - 6 corresponding to an axis orthogonal to the first and second axes;
  - 7 (b) defining at least one region within a two-dimensional array, said at least one
  - 8 region having at least one element for analysis;
  - 9 (c) defining a morphological mask having two dimensions and having at least one
  - 10 element, said morphological mask having at least one set element and at least one test
  - 11 element;
  - 12 (d) defining a two-dimensional output array corresponding to a selected two-
  - 13 dimensional array containing elements for analysis;
  - 14 (e) orienting said morphological mask with respect to said selected two-dimensional
  - 15 array containing said region having elements for analysis and with respect to at least one
  - 16 of a predecessor two-dimensional array and a successor two-dimensional array;
  - 17 (f) computing, using a mathematical operation, a result based on the properties of
  - 18 said at least one set element and the corresponding elements of said selected two-
  - 19 dimensional array containing elements for analysis and said at least one of a predecessor
  - 20 two-dimensional array and a successor two-dimensional array;
  - 21 (g) plotting the computed result in the two-dimensional output array at one or more
  - 22 elements corresponding to said at least one test element of said morphological mask; and
  - 23 (h) repeating steps (e), (f) and (g) while moving said morphological mask stepwise
  - 24 along said first axis and said second axis over said region having elements for analysis
  - 25 until every element of said region has been analyzed.
- 1 2. The method of claim 1, further comprising repeating steps (d) through (h) until every
- 2 region within successive two-dimensional arrays of said three-dimensional subset has been
- 3 analyzed.
- 1 3. The method of claim 1, wherein said first axis and said second axis representing elements
- 2 within the two-dimensional arrays are rows and columns.

- 1    4.     The method of claim 1, wherein said two-dimensional arrays are video frames.
- 1    5.     The method of claim 1, wherein said third dimension corresponding to an axis orthogonal  
2    to the first and second axes represents time.
- 1    6.     The method of claim 1, wherein said third dimension corresponding to an axis orthogonal  
2    to the first and second axes represents frame sequence numbers.
- 1    7.     The method of claim 1, wherein the mathematical operation corresponds to taking the  
2    highest incidence of occurrence in a histogram.
- 1    8.     The method of claim 1, wherein the mathematical operation corresponds to assigning a  
2    value if and only if the value is the only value that appears at elements corresponding to the at  
3    least one test element of the morphological mask.
- 1    9.     The method of claim 1, further comprising recording the plotted result as a computer-  
2    readable file.
- 1    10.    The method of claim 1, further comprising displaying the plotted result.
- 1    11.    A method for filling a connected three-dimensional digital volume, the method  
2    comprising:
  - 3        (a)     selecting a plurality of sequential two-dimensional sections that contain the  
4               volume, said two dimensional sections disposed orthogonally to a third  
5               dimension, each two-dimensional section containing locations identified by a first  
6               coordinate and a second coordinate;
  - 7        (b)     defining a plurality of regions in at least one of said two-dimensional sections,  
8               each region comprising at least one location;
  - 9        (c)     selecting a first region in one of said at least one of said two-dimensional sections,  
10              said region included within said volume to be filled with a selected symbol;
  - 11        (d)     filling said selected first region with said selected symbol;
  - 12        (e)     moving in a first direction along said third dimension to the successive two-  
13              dimensional section;

- 58 -

- (f) determining whether a location in the successive two-dimensional section corresponding to a filled location in said one of said at least one of said two-dimensional sections belongs to said volume;
- (1) if there is a positive outcome of said determination step:
- (i) filling a region that includes said location in said successive two-dimensional section with said selected symbol; and
- (ii) beginning with said newly-filled region in said successive two-dimensional section, repeating said moving, determining and filling steps recited immediately heretofore until said determining step results in a negative outcome; and
- (g) upon a negative outcome of any determining step heretofore, returning to said first region, and, moving along said third dimension in a direction opposite to said first direction, repeating the steps of moving, determining and filling as stated above until a negative outcome results for a determining step.

12. The method of claim 11, wherein the two-dimensional sections comprise images.

13. The method of claim 12, wherein the first coordinate and the second coordinate define the location of a pixel.

14. The method of claim 12, wherein the first coordinate and the second coordinate define rows and columns of an image.

15. The method of claim 11, wherein the third dimension comprises time.

16. The method of claim 11, wherein the symbol represents a visual effect when rendered on a display.

17. A method of generating an outline of a two-dimensional region, comprising the steps of:

(a) defining a two-dimensional region within a two dimensional array containing elements represented by a first axis and a second axis that is non-collinear with said first axis;

- (b) defining a morphological mask having at least two dimensions and having at least one element, said morphological mask having at least one set element and at least one test element;
- (c) defining a two-dimensional output array corresponding to said two-dimensional array containing said region;
- (d) orienting said morphological mask with respect to said two-dimensional array containing said region;
- (e) computing a result based on the properties of said at least one set element of said morphological mask and the corresponding elements of said two-dimensional array containing said region, the result being to turn off the test elements of said morphological mask if and only if a condition selected from the group of conditions consisting of all of the set elements of the mask are in positions corresponding to elements of the region and none of the set elements of the mask are in positions corresponding to elements of the region is true, and the result being to set the test elements of the morphological mask otherwise;
- (f) plotting the computed result in the two-dimensional output array at one or more elements corresponding to said at least one test element of said morphological mask; and
- (g) repeating steps (e) and (f) while moving said morphological mask stepwise along said first axis and said second axis over the portion of the two-dimensional array containing said region until every element of said region has been analyzed.

18. The method of claim 17, wherein said first axis and said second axis representing elements within the two-dimensional arrays are rows and columns.

19. The method of claim 17, wherein said two-dimensional arrays are video frames.

20. The method of claim 17, further comprising recording the plotted result as a computer-readable file.

21. The method of claim 17, wherein the morphological mask comprises a square array having an odd number of elements, and the test element is the center element.

22. The method of claim 21, wherein the elements of the morphological mask are pixels.



1 23. A method of generating an outline of at least one two-dimensional region, comprising the  
2 steps of:

- 3 (a) defining a plurality of two-dimensional regions within a two dimensional array  
4 containing elements represented by a first axis and a second axis that is non-collinear  
5 with said first axis;
- 6 (b) defining a morphological mask having at least two dimensions and having at least one  
7 element, said morphological mask having at least one set element and at least one test  
8 element;
- 9 (c) defining a two-dimensional output array corresponding to said two-dimensional array  
10 containing said plurality of regions;
- 11 (d) selecting at least one of said plurality of regions, each of said selected regions to have  
12 an outline generated therefor;
- 13 (e) orienting said morphological mask with respect to said two-dimensional array  
14 containing said plurality of regions;
- 15 (f) computing a result based on the properties of said at least one set element of said  
16 morphological mask and the corresponding elements of said two-dimensional array  
17 containing said plurality of regions, the result being to turn off the test elements of  
18 said morphological mask if and only if a condition selected from the group of  
19 conditions consisting of all of the set elements of the mask are in positions  
20 corresponding to elements of said at least one selected region and none of the set  
21 elements of the mask are in positions corresponding to elements of said at least one  
22 selected region is true, and the result being to set the test elements of the  
23 morphological mask otherwise;
- 24 (g) plotting the computed result in the two-dimensional output array at one or more  
25 elements corresponding to said at least one test element of said morphological mask;  
26 and
- 27 (h) repeating steps (f) and (g) while moving said morphological mask stepwise along said  
28 first axis and said second axis over the portion of the two-dimensional array  
29 containing said at least one selected region until every element of said at least one  
30 selected region has been analyzed.

1 24. The method of claim 23, wherein said first axis and said second axis representing  
2 elements within the two-dimensional arrays are rows and columns.

1 25. The method of claim 23, wherein said two-dimensional arrays are video frames.

1 26. The method of claim 23, further comprising recording the plotted result as a computer-  
2 readable file.

1 27. The method of claim 23, wherein the morphological mask comprises a square array  
2 having an odd number of elements, and the test element is the center element.

1 28. The method of claim 27, wherein the elements of the morphological mask are pixels.

1 29. A method of encoding at least a portion of an image, comprising the steps of:

2 (a) defining a region of an image having pixels at locations identifiable by two non-  
3 collinear axes, each pixel having an appearance;

4 (b) analyzing axis-wise said pixels to determine sequences of pixels having  
5 substantially identical appearance;

6 (c) comparing a sequence of pixels occurring along a first axis-wise traverse with a  
7 sequence of pixels occurring along a successive axis-wise traverse;

8 (d) in the event that said comparison discloses two or more successive traverses  
9 having an identical number of distinct appearances in an identical progression, recording  
10 a number corresponding to the number of such successive traverses, recording for said  
11 first traverse a series of ordered pairs comprising a first value representing the appearance  
12 and a second value representing the number of successive pixels having said appearance,  
13 and recording for each successive traverse a series of values corresponding to said second  
14 value of each ordered pair;

15 (e) in the event that said comparison fails to discloses two or more successive  
16 traverses having an identical number of distinct appearances in an identical progression,  
17 recording the number one and recording for said traverse a series of ordered pairs  
18 comprising a first value representing the appearance and a second value representing the  
19 number of successive pixels having said appearance; and

20 (f) repeating steps (c), (d) and (e) until said pixels of said region are completely  
21 encoded.

- 62 -

1 30. The method of claim 29 wherein said axis-wise traverse comprises traversing a selected  
2 one of a row and a column.

1 31. A method of decoding an encoded image, comprising the steps of:

2 (a) reading from a memory a location of a region within an image, said region defined by  
3 one or more pixels at locations identifiable by two non-collinear axes, each pixel having  
4 an appearance;

5 (b) reading from said memory a number corresponding to the number of successive  
6 traverses along one of said two non-collinear axes, said traverses having an identical  
7 number of distinct appearances in an identical progression;

8 (c) reading a series of ordered pairs comprising a first value representing an appearance  
9 and a second value representing the number of successive pixels having said appearance

10 (d) rendering pixels along said traverse according to said series of ordered pairs;

11 (e) in the event that said number read in step (b) is greater than one, repeating a number  
12 of times equal to said number read in step (b) reduced by one the steps of:

13 (1) reading from memory a series of values corresponding to said second value of  
14 each ordered pair read in step (c); and

15 (2) for each such value read in step (e)(1), rendering a sequences of pixels  
16 corresponding to said second value, each pixel having an appearance

17 corresponding to said first value of said ordered pair read in step (c); and

18 (f) repeating steps (b) through (e) until said pixels of said region are completely  
19 rendered.

1 32. The method of claim 31 wherein said axis-wise traverse comprises traversing a selected  
2 one of a row and a column.

1 33. The method of claim 31 wherein rendering a pixel comprises displaying said pixel using  
2 at least one of a color, a brightness, a blinking, a flashing, and a display mode.

1 34. The method of claim 31 further comprising the step of recording on a computer-readable  
2 medium a representation of said rendering of pixels in said region.

1 35. A method of encoding at least a portion of an image, comprising the steps of:

- (a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance;
- (b) analyzing axis-wise said pixels to determine sequences of pixels having substantially identical appearance;
- (c) in the event that said analysis discloses two or more successive pixels having identical appearance, recording a series of ordered triples comprising a first value representing said appearance, a second value representing the number of successive pixels having said appearance, and a third value representing an offset defining a starting position of said two or more successive pixels with respect to a pixel at a known position.

36. The method of claim 35 wherein defining two non-collinear axes comprises defining a row and a column.

37. The method of claim 35 wherein analyzing a pixel to determine an appearance comprises analyzing for at least one of a color, a brightness, and a display mode.

38. A method of decoding at least a portion of an image, comprising the steps of:

- (a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance;
- (b) reading a series of ordered triples comprising a first value representing said appearance, a second value representing the number of successive pixels having said appearance, and a third value representing an offset defining a starting position of said two or more successive pixels with respect to a pixel at a known position; and
- (c) for each ordered triple, rendering pixels in said region using said appearance said number of successive pixels having said appearance beginning at said starting position with respect to a pixel at a known position.

39. The method of claim 38 wherein defining two non-collinear axes comprises defining a row and a column.

40. The method of claim 38 wherein rendering a pixel comprises displaying said pixel using at least one of a color, a brightness, a blinking, a flashing, and a display mode.

- 64 -

1 41. The method of claim 38 further comprising the step of recording on a computer-readable  
2 medium a representation of said rendering of pixels in said region.

1 42. A method of encoding at least a portion of an image, comprising the steps of:

2 (a) defining a region of an image having pixels at locations identifiable by two non-  
3 collinear axes, each pixel having an appearance;

4 (b) defining pixels in said image that represent a background, said background having a  
5 characteristic background appearance;

6 (d) comparing a sequence of pixels occurring along a first axis-wise traverse with a  
7 sequence of pixels occurring along a successive axis-wise traverse;

8 (e) in the event that said comparison discloses two or more successive traverses  
9 having an identical number of distinct appearances in an identical progression:

10 (i) recording a number N corresponding to the number of such successive  
11 traverses;

12 (ii) for the first of such successive traverses, recording for each sequence of pixels  
13 having a distinct appearance different from said characteristic background  
14 appearance an ordered triple comprising a first value representing said  
15 appearance, a second value representing the number of successive pixels  
16 having said appearance, and a third value representing an offset defining a  
17 starting position of said two or more successive pixels with respect to a pixel  
18 at a known position;

19 (iii) for the following of said N minus one traverses, recording for each sequence  
20 of pixels having a distinct appearance different from said characteristic  
21 background appearance an ordered double comprising a first quantity  
22 representing the number of successive pixels having said appearance indicated  
23 by the first value of the ordered triple recorded for the corresponding  
24 sequence of pixels in the first traverse, and a second quantity representing an  
25 offset defining a starting position of said two or more successive pixels with  
26 respect to a pixel at a known position;

27 (f) in the event that said comparison fails to disclose two or more successive  
28 traverses having an identical number of distinct appearances in an identical progression,  
29 recording the number one and recording for said traverse a series of ordered triples  
30 comprising a first value representing an appearance different from said characteristic  
31 background appearance, a second value representing the number of successive pixels

- 65 -

having said appearance, and a third value representing an offset defining a starting position of said two or more successive pixels with respect to a pixel at a known position; and

(g) repeating steps (c), (d) and (e) until said pixels of said region having an appearance different from said characteristic background appearance are completely encoded.

43. The method of claim 42 wherein defining two non-collinear axes comprises defining a row and a column.

44. The method of claim 42 wherein analyzing a pixel to determine an appearance comprises analyzing for at least one of a color, a brightness, and a display mode.

45. A method of decoding at least a portion of an image, comprising the steps of:

(a) defining a region of an image having pixels at locations identifiable by two non-collinear axes, each pixel having an appearance;

(b) defining a characteristic background appearance;

(c) reading from a record a number N corresponding to a number of successive traverses having an identical number of distinct appearances in an identical progression;

(d) if the number N is one:

(1) reading for said traverse a series of ordered triples comprising a first value representing an appearance different from said characteristic background appearance, a second value representing the number of successive pixels having said appearance, and a third value representing an offset defining a starting position of said two or more successive pixels with respect to a pixel at a known position; and

(2) for each ordered triple, rendering with said appearance said number of successive pixels having said appearance beginning at said starting position with respect to a pixel at a known position;

(e) if the number N is greater than one, for the first traverse, performing steps (d)(1) and (d)(2), and for each traverse of the further N minus one traverses:

(1) reading for each traverse a series of ordered doubles comprising a first quantity representing the number of successive pixels having said appearance indicated by the first value of the ordered triple recorded for the corresponding sequence of pixels in the first traverse, and a second quantity representing an offset defining a

- 66 -

22 starting position of said two or more successive pixels with respect to a pixel at a  
23 known position; and  
24 (2) for each ordered double, rendering with said appearance said number of  
25 successive pixels having said appearance beginning at said starting position with  
26 respect to a pixel at a known position;  
27 (f) repeating steps (c), (d) and (e) until said pixels of said region having an appearance  
28 different from said characteristic background appearance are completely encoded.  
29 and  
30 (g) for any pixel in said region of said image that has not been rendered in steps (d), (e)  
31 and (f), rendering said pixel using a characteristic background appearance.

1 46. The method of claim 45 wherein defining two non-collinear axes comprises defining a  
2 row and a column.

1 47. The method of claim 45 wherein rendering a pixel comprises displaying said pixel using  
2 at least one of a color, a brightness, a blinking, a flashing, and a display mode.

1 48. The method of claim 45 further comprising the step of recording on a computer-readable  
2 medium a representation of said rendering of pixels in said region.




FIG. 1A




FIG. 1B





FIG. 1C



5 FIG. 1D






FIG. 2

3/18








FIG. 2A



5/18



48

FIG. 3

6/18





FIG. 4

54

FIG. 5-1	FIG. 5-2
-------------	-------------

FIG. 5







FIG. 5-2



**FIG. 5A**



10/18




FIG. 6




FIG. 7

12/18



FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G




FIG. 9A

NO. ROWS (=3)  
 ROW 1: (COLOR<sub>1</sub>, N<sub>1</sub>), (COLOR<sub>2</sub>, N<sub>2</sub>), (COLOR<sub>3</sub>, N<sub>3</sub>), ... (COLOR<sub>N</sub>, N<sub>N</sub>)  
 ROW 2: N<sub>1</sub>, N<sub>2</sub>, N<sub>3</sub>, ..., N<sub>N</sub>  
 ROW 3: N<sub>1</sub>, N<sub>2</sub>, N<sub>3</sub>, ..., N<sub>N</sub>

FIG. 9B

(VALUE INDICATOR OF COLOR, RUN LENGTH, OFFSET)

FIG. 9C

NO. ROWS (=3)

ROW 1: (COLOR<sub>1</sub>, RUNLENGTH<sub>1</sub>, OFFSET<sub>1</sub>), (COLOR<sub>2</sub>, RUNLENGTH<sub>2</sub>, OFFSET<sub>2</sub>)  
.....(COLOR<sub>N</sub>, RUNLENGTH<sub>N</sub>, OFFSET<sub>N</sub>)

ROW 2: (RUNLENGTH<sub>1</sub>, OFFSET<sub>1</sub>), (RUNLENGTH<sub>2</sub>, OFFSET<sub>2</sub>), ....(RUNLENGTH<sub>N</sub>, OFFSET<sub>N</sub>)

ROW 3: (RUNLENGTH<sub>1</sub>, OFFSET<sub>1</sub>), (RUNLENGTH<sub>2</sub>, OFFSET<sub>2</sub>), ....(RUNLENGTH<sub>N</sub>, OFFSET<sub>N</sub>)

FIG. 9D

14/18




FIG. 10A




FIG. 10B




FIG. 11A





FIG. 11B

16/18






FIG. 12A




FIG. 12B



18/18




FIG. 13



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 September 2001 (07.09.2001)

PCT

(10) International Publication Number  
**WO 01/65420 A3**

(51) International Patent Classification?: H04N 7/26, I/417

(21) International Application Number: PCT/US01/06411

(22) International Filing Date: 28 February 2001 (28.02.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/185.668	29 February 2000 (29.02.2000)	US
60/229.241	30 August 2000 (30.08.2000)	US
60/233.340	18 September 2000 (18.09.2000)	US
09/694.079	20 October 2000 (20.10.2000)	US

(71) Applicant: WATCHPOINT MEDIA, INC. [US/US]: 129 South Street, Boston, MA 02111 (US).

(72) Inventors: SARACHIK, Karen: 472 Walnut Street, Newton, MA 02460 (US). DAKSS, Jon: 158 Thorndike Street,

Cambridge, MA 02141 (US). BOVE, V., Michael, Jr.: 57 Ray Road, Wrentham, MA 02093 (US). WACHMAN, Josh: 135 Pleasant Street, #505, Brookline, MA 02446 (US). KATCHER, Dan: 125 Brookside Road, Needham, MA 02492 (US).


(74) Agent: MILSTEIN, Joseph, B.: Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian

[Continued on next page]


(54) Title: METHODS FOR MANIPULATING DATA IN MULTIPLE DIMENSIONS




A



B



C



5

D

(57) Abstract: A system and method of adding hyperlinked information to a television broadcast. The broadcast material is analyzed and one or more regions within a frame are identified. Additional information can be associated with a region, and can be transmitted in encoded form, using timing information to identify the frame with which the information is associated. The system comprising a video source and an encoder that produces a transport stream in communication with the video source, an annotation source, a data packet stream generator that produces encoded annotation data packets in communication with the annotation source and the encoder, and a multiplexer system in communication with the encoder and the data packet stream generator. The encoder provides timestamp information to the data packet stream generator and the data packet stream generator synchronizes annotation data from the annotation source with a video signal from the video source in response to the timestamp information. The multiplexer generates a digital broadcast signal that includes an augmented transport stream from the transport stream and the encoded data packets. A receiver displays the annotation information associated with the video signal in response to a viewer request on a frame by frame basis. A viewer can respond interactively to the material, including performing commercial transactions, by using a backchannel that is provided for interactive communication.

WO 01/65420 A3



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:

28 February 2002

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

# INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/US 01/06411

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H04N7/26 H04N1/417

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T G06F H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 969 755 A (COURTNEY JONATHAN D) 19 October 1999 (1999-10-19) abstract column 4, line 54 -column 9, line 4 column 12, line 6 - line 40 column 13, line 24 - line 45 claims 1-3,7,12-14,16,18,22 figures 4,5	1-6,8-10
A	---	7,11-28
X	BRIGGER P ET AL: "Morphological shape representation for very low bit-rate video coding", SIGNAL PROCESSING. IMAGE COMMUNICATION,NL,ELSEVIER SCIENCE PUBLISHERS, AMSTERDAM, VOL. 7, NR. 4, PAGE(S) 297-311 XP004047086 ISSN: 0923-5965 paragraphs '0001!,'0004!,'0006! ---	11-28
A	--- -/--	1-10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in contact with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*B\* document member of the same patent family

Date of the actual completion of the international search

3 December 2001

Date of mailing of the international search report

13. 12. 2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.  
Fax. (+31-70) 340-3016

Authorized officer

Beaudet, J-P

# INTERNATIONAL SEARCH REPORT

Int. tional Application No

PCT/US 01/06411

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	BOVE V M ET AL: "ADDING HYPERLINKS TO DIGITAL TELEVISION", SMPTE JOURNAL, SMPTE INC. SCARSDALE, N.Y,US, VOL. 108, NR. 11, PAGE(S) 795-801 XP000955410 ISSN: 0036-1682 the whole document	1-28
A	MONTSE PARDÀS, PHILIPPE SALEMBIER, LUÍS TORRES: "3D Morphological Segmentation for Image Sequence Processing" NONLINEAR DIGITAL SIGNAL PROCESSING, 'Online! 17 - 20 January 1993, pages 6.1_3.1-6.1_3.6 , XP002174667 Barcelona, Spain Retrieved from the Internet: <URL:http://ieeexplore.ieee.org/iel5/6208/16581/00767733.pdf> 'retrieved on 2001-07-16! abstract paragraph '0002!	1-28
A	SALEMBIER P ET AL: "SEGMENTATION-BASED VIDEO CODING SYSTEM ALLOWING THE MANIPULATION OF OBJECTS" IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, IEEE INC. NEW YORK, US, vol. 7, no. 1, 1 February 1997 (1997-02-01), pages 60-73, XP000678880 ISSN: 1051-8215 the whole document	1,11,17, 23
A	VASS J, PALANIAPPAN K, XINHUA ZHUANG: "AUTOMATIC SPATIO-TEMPORAL VIDEO SEQUENCE SEGMENTATION" PROCEEDINGS 1998 INTERNATIONAL CONFERENCE ON IMAGE PROCESSING., 'Online! 4 - 7 October 1998, pages 958-962, XP002174668 Chicago, IL, USA Retrieved from the Internet: <URL:http://ieeexplore.ieee.org/iel4/5852/15617/00723681.pdf> 'retrieved on 2001-07-16! abstract paragraph '0002!	1-28
X	US 5 883 975 A (MATSUURA KAZUNORI ET AL) 16 March 1999 (1999-03-16) column 17, line 12 -column 18, line 3; figures 4,5 column 24, line 21 -column 25, line 17; figures 13,14	29-48

-/--

# INTERNATIONAL SEARCH REPORT

Int. Application No  
PCT/US 01/06411

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 04, 30 April 1999 (1999-04-30) & JP 11 027540 A (OKI DATA:KK), 29 January 1999 (1999-01-29) abstract	35-41
A	EP 0 498 511 A (OCE NEDERLAND BV) 12 August 1992 (1992-08-12) abstract	29-48
A	NAKANISHI I ET AL: "AN IMAGE REDUCTION METHOD USING MR CODES", SYSTEMS & COMPUTERS IN JAPAN, SCRIPTA TECHNICA JOURNALS. NEW YORK, US, VOL. 28, NR. 7, PAGE(S) 1-10 XP000723790 ISSN: 0882-1666 paragraphs '02.1!', '03.0!	29-48
A	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 10, 30 November 1995 (1995-11-30) & JP 07 170410 A (KOKUSAI ELECTRIC CO LTD), 4 July 1995 (1995-07-04) abstract	29-48
A	PATENT ABSTRACTS OF JAPAN vol. 004, no. 181 (E-037), 13 December 1980 (1980-12-13) & JP 55 124361 A (NIPPON TELEGR & TELEPH CORP), 25 September 1980 (1980-09-25) abstract	29-48

**Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)**

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
  
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
  
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

**Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)**

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

**Remark on Protest**

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.



**FURTHER INFORMATION CONTINUED FROM PCT/SA/ 210**

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-10, 11-16, 17-22, 23-28

relate to region correspondence problem in a video sequence (see description page 13, line 11-23).

2. Claims: 29-30, 31-37, 38-41, 42-44, 45-48

relate to space optimization for filing (see description page 40, line 24).

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

PCT/US 01/06411

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5969755	A	19-10-1999	EP	0805405 A2	05-11-1997
			JP	10084525 A	31-03-1998
US 5883975	A	16-03-1999	JP	8084260 A	26-03-1996
			JP	8130651 A	21-05-1996
			JP	8130652 A	21-05-1996
JP 11027540	A	29-01-1999	US	6301300 B1	09-10-2001
EP 0498511	A	12-08-1992	NL	9100225 A	01-09-1992
			DE	69210274 D1	05-06-1996
			DE	69210274 T2	19-12-1996
			EP	0498511 A1	12-08-1992
			JP	3113035 B2	27-11-2000
			JP	5030365 A	05-02-1993
			US	5319469 A	07-06-1994
JP 07170410	A	04-07-1995	NONE		
JP 55124361	A	25-09-1980	JP	1300523 C	31-01-1986
			JP	60026347 B	22-06-1985